

## EUROLITE LED TMH-X18 Moving-Head Beam

Beam spotlight with 1° beam angle, 150 W LED, color wheel, gobos and rotating prism

Art. No.: 51785908

GTIN: 4026397632910



### Features:

- Equipped with a white 150 W COB LED
- Lightbeam with 1° radiation angle
- Positioning within 540° PAN and 270° TILT
- Exact positioning via 16 bit PAN/TILT movement resolution
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Rotating 8-facet prism
- The prism rotates in both directions and at different speeds
- Frost-filter
- Strobe effect with 1-18 flashes per second
- Internal programs
- Dimmer
- Motorized focus
- Automatic position correction
- Control board with LCD and foil-keyboard for adjusting the DMX-starting address, PAN/TILT-Reverse, Program, Reset
- P-Con terminals for power linking up to 8 units
- 1 LED 150 W COB (chip-on-board) color wheel
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo wheel with static gobos; prism 8-fold; frost filter; focus motor-driven
- Strobe effect
- Color wheel with 13 dichroic filters plus open<BR>switchable color change (mode 1: only full colors, mode 2: color-change at every position); rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 13 gobos und open<BR>shake effect
- The device is cooled by cooling fan

### Logistic

EAN / GTIN: 4026397632910

Weight: 16,80 kg

Length: 0.45 m

Width: 0.43 m

Height: 0.57 m

- Control via DMX; stand-alone; sound to light via microphone
- Fixtures available for Light J; LED PC-Control 512; Light Captain
- Flicker-free
- With a beam angle of 1°

## Technical specifications:

|                         |   |
|-------------------------|---|
| Power supply:           | 100-240 V AC, 50/60 Hz  |
| Power consumption:      | 210 W   |
| IP classification:      | IP20  |
| Power connection:       | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug (provided)   |
| Power output:           | 1 x P-Con (gray), mounting version  |
| Lamp type:              | LED lamp  |
| LED type:               | 1 x 150 W COB (chip-on-board) color wheel   |
| Max. TILT movement:     | 270° exact positioning (16 bit resolution) auto<br>position correction (feedback)   |
| Max. PAN movement:      | 540° exact positioning (16 bit resolution) auto<br>position correction (feedback)   |
| Flash rate:             | 0 - 18 Hz   |
| Equipment:              | Gobo wheel with static gobos; prism 8-fold; frost<br>filter; focus motor-driven   |
| Color generation:       | Color wheel with 13 dichroic filters plus open<br>Switchable color change (mode 1: only full colors,<br>mode 2: color-change at every position); rainbow<br>effect with adjustable speed in both directions |
| Gobos:                  | Gobo wheel with static gobos, 13 gobos und open<br>Shake effect   |
| DMX channels:           | 14  |
| DMX input:              | 1 x 3-pin XLR (M) mounting version  |
| DMX output:             | 1 x 3-pin XLR (F) mounting version  |
| Cooling:                | Cooling fan   |
| Control:                | DMX; stand-alone; sound to light via microphone   |
| Fixtures available for: | Light J; LED PC-Control 512; Light Captain  |
| Projection:             | Flicker-free  |
| Beam angle:             | 1°  |
| Beam angle (1/2 peak):  | 1°  |
| Color temperature:      | 6000K   |
| Housing color:          | Black   |
| Dimensions:             | Width: 33 cm<br>Depth: 34 cm<br>Height: 45 cm   |
| Weight:                 | 14.5 kg   |
| Special product:        | Not designed for household room illumination  |
| Intended use:           | Show effect lighting  |

**Scope of delivery:**

---

1 x omega bracket