

## EUROLITE LED TMH-X4 Moving Head Wash Zoom

Washlight with 19 x 15 W LEDs, 4in1 QCL RGBW-Farbmischung and motorized zoom

Art. No.: 51785915

GTIN: 4026397664591



**List price: 760.41 €**

incl. 19% VAT.

### Features:

- 19 powerful LEDs 15 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix) <BR>3 segments controlled separately
- Positioning within 540° PAN and 270° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor-driven
- Integrated show programs
- The device is cooled by temperature-controlled fan at the Head; cooling fan at the Base
- Control via stand-alone; DMX; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 1° - 40°
- Multicolor LCD display
- Color blend stepless; color change adjustable; Dimmer electronic
- Strobe effect
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Wedding/gala/events; Stage; mobile djs / entertainer; Rental
- Application possibility: Standing; suspended

#### Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 2 x omega bracket

### Logistic

EAN / GTIN: 4026397664591

Weight: 9,40 kg

Length: 0.45 m

Width: 0.27 m

Height: 0.40 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	225 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 2 A Fuse replaceable
Lamp type:	LED lamp
LED:	19 x 15 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
Max. TILT movement:	270° Exact positioning (16 bit resolution) Auto position correction (feedback)
Max. PAN movement:	540° Exact positioning (16 bit resolution) Auto position correction (feedback)
Equipment:	Zoom motor-driven
DMX channels:	16; 24
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan at the Head Cooling fan at the Base
Control:	Stand-alone; DMX; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light J; LED PC-Control 512; EASY SHOW 1; Light Captain
Projection:	Flicker-free
Beam angle:	1° - 40°
Beam angle (1/2 peak):	1 - 25°
Beam angle (1/10 peak):	8 - 40°
Illuminance in Lux (lx):	Narrow red (R) 3m: 2779 lx, 6m: 763 lx Narrow green (G) 3m: 7893 lx, 6m: 1841 lx Narrow blue (B) 3m: 1468 lx, 6m: 390 lx Narrow cold white (CW) 3m: 9558 lx, 6m: 2468 lx Narrow all 3m: 19553 lx, 6m: 5001 lx Wide red (R) 3m: 272 lx, 6m: 73 lx Wide green (G) 3m: 583 lx, 6m: 160 lx Wide blue (B) 3m: 117 lx, 6m: 34 lx Wide cold white (CW) 3m: 740 lx, 6m: 211 lx Wide all 3m: 1568 lx, 6m: 439 lx
Housing color:	Black
Display type:	Multicolor LCD display
Dimensions:	Width: 30,5 cm Depth: 20,0 cm Height: 40,0 cm
Weight:	8,62 kg

Noise classification:	Class 3 (clearly perceptible sounds)
Photobiological safety:	Risk Group 0
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting