

## EUROLITE LED TMH-W555 Moving Head Wash Zoom

Washlight with 37 bright 15 W RGBW LEDs, zoom, macros, patterns and color temperature setting

Art. No.: 51785920

GTIN: 4026397693706



**List price: 1188.81 €**

incl. 19% VAT.

### Features:

- Individually controllable segments
- Positioning within 540° PAN and 270° TILT
- Functions: stepless RGBW color mixture, internal programs, automatic color changes, preset colors, color temperature setting, animated and static patterns, macros, strobe effect with variable speed, random strobe effect, dimmer
- Variable color temperature 2500-10000 K
- Automatic position correction
- Exact positioning via 16 bit PAN/TILT movement resolution
- Mains input and output for power linking up to 4 units
- 37 powerful LEDs 15 W 4in1 QCL RGBW (homogenous color mix)
- Can be operated in 24; 36; 48 CH mode
- The device is cooled by temperature-controlled fan at the Head; cooling fan at the Base
- Controlling by DMX; stand-alone; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Sound to light
- Preprogrammed in Light Captain
- Flicker-free projection
- With a beam angle of 1 - 38°
- Multicolor LCD display for easy controlling

### Logistic

EAN / GTIN: 4026397693706

Weight: 15,40 kg

Length: 0.47 m

Width: 0.36 m

Height: 0.47 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 490 W

IP classification:	IP20
Protection class:	Class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 4 A Fuse replaceable
Lamp type:	LED lamp
LED:	37 x 15 W 4in1 QCL RGBW (homogenous color mix)
Max. TILT movement:	Exact positioning (16 bit resolution) 270°
Max. PAN movement:	Exact positioning (16 bit resolution) 540°
Equipment:	Zoom motor-driven
DMX channels:	24; 36; 48
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan at the Head Cooling fan at the Base
Control:	DMX; stand-alone; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Light Captain; Sound to light
Beam angle:	1 - 38°
Beam angle (1/2 peak):	1 - 20°
Beam angle (1/10 peak):	8 - 38°
Illuminance in Lux (lx):	Narrow red (R) 1m: 14703 lx, 3m: 6338 lx, 6m: 1581 lx Narrow green (G) 1m: 36582 lx, 3m: 14313 lx, 6m: 3581 lx Narrow blue (B) 1m: 4622 lx, 3m: 2444 lx, 6m: 666 lx Narrow cold white (CW) 1m: 47065 lx, 3m: 15572 lx, 6m: 3872 lx Narrow all 3m: 35914 lx, 6m: 9025 lx Wide red (R) 1m: 4769 lx, 3m: 624 lx, 6m: 165 lx Wide green (G) 1m: 10949 lx, 3m: 1431 lx, 6m: 386 lx Wide blue (B) 1m: 2021 lx, 3m: 274 lx, 6m: 77 lx Wide cold white (CW) 1m: 11357 lx, 3m: 1505 lx, 6m: 397 lx Wide all 1m: 27092 lx, 3m: 3575 lx, 6m: 956 lx
Housing color:	Black
Display type:	Multicolor LCD display
Dimensions:	Width: 39,0 cm Depth: 26,5 cm Height: 47,5 cm
Weight:	13,90 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting