

EUROLITE LED TMH-H240 Beam/Wash/Flower Effect

Hybrid moving head with RGBW LEDs, zoom, macros, patterns and color temperature presets

Art. No.: 51785925

GTIN: 4026397710779



List price: 831.81 €

incl. 19% VAT.

Features:

- 3in1 moving head beam, wash and flower effect in one device
- 6 powerful LEDs 40 W 4in1 QCL RGBW (homogenous color mix)
 LEDs controlled separately
- Positioning within 540° PAN and 240° TILT
- PAN angle switchable between 540° and 360°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor-driven; lens rotation
- Color blend stepless; color change; colors preset; patterns preset; background color adjustable; Dimmer speed (step response) adjustable
- Strobe effect; fan effect; flower effect; multi beam effect
- Integrated show programs
- The device is cooled by temperature-controlled fan
- Control via stand-alone; Sound to light via Microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Master/slave function
- Flicker-free
- With a beam angle of 2° - 40°
- With Omega bracket
- LCD display
- Preprogrammed in Light Captain; EASY SHOW 3; Light´J
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Wedding/gala/events; Party room; mobile djs / entertainer; Stage
- Application possibility: Standing; suspended

Package contents

Logistic

EAN / GTIN: 4026397710779

Weight: 6,60 kg

Length: 0.31 m

Width: 0.23 m

Height: 0.42 m

- 1 x moving light, 1 x user manual, 1 x power cord, 2 x omega bracket, 1 x xLR cable

Technical specifications:

| | |
|--------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 190 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | P-Con (gray), mounting version |
| Fuse: | 5 x 20 mm, T 3 A |
| Lamp type: | LED lamp |
| LED: | 6 x 40 W 4in1 QCL RGBW (homogenous color mix) |
| Max. TILT movement: | 240° Exact positioning (16 bit resolution) Auto position correction (feedback) |
| Max. PAN movement: | 540°, 360° Exact positioning (16 bit resolution) Auto position correction (feedback) |
| Flash rate: | 1 - 25 Hz |
| Equipment: | Zoom motor-driven; lens rotation |
| DMX channels: | 16; 21; 24; 32; 56 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Temperature-controlled fan |
| Control: | Stand-alone; Sound to light via Microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Master/slave function |
| Preprogrammed in: | Light Captain; EASY SHOW 3; Light´J |
| Projection: | Flicker-free |
| Beam angle: | 2° - 40° |
| Beam angle (1/2 peak): | 2 - 25° |
| Beam angle (1/10 peak): | 8 - 40° |
| Illuminance in Lux (lx): | Narrow red (R) 1m: 11423 lx, 3m: 5703 lx, 6m: 1423 lx Narrow green (G) 1m: 28573 lx, 3m: 11882 lx, 6m: 2992 lx Narrow blue (B) 1m: 3089 lx, 3m: 1835 lx, 6m: 513 lx Narrow cold white (CW) 1m: 35392 lx, 3m: 15489 lx, 6m: 3899 lx Narrow all 1m: 67721 lx, 3m: 30843 lx, 6m: 7807 lx |
| Housing color: | Black |
| Attachment system: | 2x Omega bracket |
| Display type: | LCD display |
| Dimensions: | Width: 26 cm Depth: 18 cm |

Height: 33 cm

Weight: 6,10 kg

Noise classification: Class 3 (clearly perceptible sounds)

Legal specifications

Special product: Not designed for household room illumination

Intended use: Show effect lighting
