

EUROLITE LED TMH-W400 Moving Head Wash Zoom

Bright washlight with 400 W COB LED and motorized zoom

Art. No.: 51785930

GTIN: 4026397700138



List price: 1069.81 €

incl. 19% VAT.

Features:

- 1 powerful LED 400 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix)
- Positioning within 540° PAN, 230° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor driven
- Color blend stepless; Dimmer electronic
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in Light Captain; Light´J
- Flicker-free
- With a beam angle of 9° - 48°
- Very high color rendering index (CRI)
- Multicolor LCD display
- Mains input and output for power linking up to 4 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; mobile djs / entertainer; rental
- Application possibility: Standing; suspended

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 2 x omega bracket

Logistic

EAN / GTIN: 4026397700138

Weight: 11,40 kg

Length: 0.48 m

Width: 0.33 m

Height: 0.37 m

Technical specifications:

| | |
|------------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 360 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | P-Con (gray), mounting version |
| Fuse: | 5 x 20 mm, T 5 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 1 x 400 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix) |
| Max. TILT movement: | 230° exact positioning (16 bit resolution) auto position correction (feedback) |
| Max. PAN movement: | 540° exact positioning (16 bit resolution) auto position correction (feedback) |
| Flash rate: | 1 - 25 Hz |
| Equipment: | Zoom motor driven |
| DMX channels: | 13 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in: | Light Captain; Light´J |
| Projection: | Flicker-free |
| Beam angle: | 9° - 48° |
| Beam angle (1/2 peak): | 9 - 25° |
| Beam angle (1/10 peak): | 16 - 48° |
| Color rendering index (CRI): | 92 Ra |
| Illuminance in Lux (lx): | Narrow red (R) 1m: 14250 lx, 3m: 2003 lx, 6m: 470 lx Narrow green (G) 1m: 36558 lx, 3m: 4533 lx, 6m: 1085 lx Narrow blue (B) 1m: 4869 lx, 3m: 959 lx, 6m: 235 lx Narrow warm white (WW) 1m: 33844 lx, 3m: 3508 lx, 6m: 837 lx Narrow all 1m: 75609 lx, 3m: 9660 lx, 6m: 2293 lx Wide red (R) 1m: 2821 lx, 3m: 359 lx, 6m: 97 lx Wide green (G) 1m: 6107 lx, 3m: 809 lx, 6m: 227 lx Wide blue (B) 1m: 1410 lx, 3m: 188 lx, 6m: 53 lx Wide warm white (WW) 1m: 5425 lx, 3m: 706 lx, 6m: 195 lx Wide all 1m: 13817 lx, 3m: 1798 lx, 6m: 495 lx |

| | |
|-----------------------|---|
| Housing color: | Black |
| Display type: | Multicolor LCD display |
| Dimensions: | Width: 30,0 cm Depth: 23,0 cm Height: 45,0 cm |
| Weight: | 10,20 kg |
| Noise classification: | Class 2 (slight noise) |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |