

## EUROLITE LED TMH FE-600 Beam/Flower Effect

RGBW Moving Head flower with large zoom range and 6 x 12 W LED

Art. No.: 51785956

GTIN: 4026397554434



**The article is no longer in our assortment.**

### Features:

- Equipped with 6 x 12 W COB LED in the colors red, green, blue and white
- Compact lightweight
- Functions: colored beams in R, G, B and W, preset colors, built-in program, strobe effect with variable speed, dimmer, sound-control, Master/Slave operation
- Adjustable zoom movement - from narrow single beam to room-filling beams - via rotating lens
- Stepless RGBW color mixture
- Positioning within 540° PAN and 190° TILT
- PAN-angle switchable between 540° and 360°
- Dimmer speed (step response) adjustable
- Automatic position correction
- Exact positioning via 16 bit PAN/TILT movement resolution
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-controlled via built-in microphone
- Control board with LC display for adjusting the DMX-starting address, PAN/TILT reverse, reset
- Switch-mode power supply for operation between 100 and 240 volts
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power up to 8 devices
- DMX512 control possible via any commercial DMX controller
- 6 powerful LEDs 12 W COB (chip-on-board) 4in1 QCL RGBW
- PAN angle switchable between 540° and 360°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Multi beam effect; beam effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; Sound to light via Microphone
- Preprogrammed in Light'J; LED PC-Control 512; Light Captain

### Logistic

EAN / GTIN: 4026397554434

Weight: 6,20 kg

Length: 0.32 m

Width: 0.29 m

Height: 0.40 m

- Flicker-free
- With a beam angle of 6,5°

#### Package contents

- 1 x moving light, 1 x omega bracket, 1 x user manual, 1 x power cord, 1 x xLR cable

### Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	90 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray)
Lamp type:	LED lamp
LED:	6 x 12 W COB (chip-on-board) 4in1 QCL RGBW
Max. TILT movement:	190° Exact positioning (16 bit resolution) Auto position correction (feedback)
Max. PAN movement:	540°, 360° Exact positioning (16 bit resolution) Auto position correction (feedback)
Flash rate:	0 - 18 Hz
DMX channels:	15
Cooling:	Cooling fan
Control:	Stand-alone; DMX; Sound to light via Microphone
Preprogrammed in:	Light'J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	6,5°
Beam angle (1/2 peak):	6,5°
Housing color:	Black
Dimensions:	Width: 24,5 cm Depth: 19 cm Height: 33 cm
Weight:	5,09 kg
DMX connection:	3-pin XLR
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting