

EUROLITE LED TMH-12 Moving Head Beam

4in1 moving head with narrow beam angle

Art. No.: 51785967

GTIN: 4026397481792



The article is no longer in our assortment.

Features:

- Equipped with 12 high-power 10 W RGBW CREE LEDs (4in1)
- Compact lightweight
- Narrow beam angle
- Positioning within 630° PAN and 200° TILT
- Stepless RGBW color mixture
- Different dimmer speeds (step response) adjustable
- Masterdimmer
- 8 internal programs can be called up via Control board
- Color-macro-function for an easy selection of possible color-combinations
- Strobe effect with 1-18 flashes per second
- Random strobe effect
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-control via built-in microphone
- Control board with graphic LCD for adjusting the DMX-starting address, PAN/TILT reverse, program, reset, operating hours
- Switch-mode power supply
- Automatic power supply adaption between 100 and 240 Volts without power selector
- DMX control via every standard DMX controller
- 12 powerful LEDs 10 W high-power 4in1 QCL RGBW (homogenous color mix)
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo effect
- The device is cooled by cooling fan
- Control via DMX; stand-alone; sound to light via microphone

Logistic

EAN / GTIN: 4026397481792

Weight: 5,85 kg

Length: 0.36 m

Width: 0.33 m

Height: 0.21 m

- Preprogrammed in Light´J; LED PC-Control 512
- With a beam angle of 9°

Package contents

- 1 x omega bracket

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	150 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	12 x 10 W high-power 4in1 QCL RGBW (homogenous color mix)
Max. TILT movement:	200° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	630° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	0 - 18 Hz
DMX channels:	12
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone; sound to light via microphone
Preprogrammed in:	Light´J; LED PC-Control 512
Beam angle:	9°
Beam angle (1/2 peak):	9°
Housing color:	Black
Dimensions:	Width: 25,5 cm Depth: 15,5 cm Height: 31 cm
Weight:	5,10 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting