

EUROLITE LED TMH-X3 Moving Head Beam

60 W beam, compact, RGBW color mixing, large zoom, 8-facet prism

Art. No.: 51785989

GTIN: 4026397594089

The article is no longer in our assortment.

Features:

- Equipped with a 60 W LED with RGBW colors from Osram
- Motorized zoom with 5-47° radiation angle
- Effect wheel with rotating 8-facet prism
- Positioning within 540° PAN and 220° TILT
- PAN angle switchable between 360° and 540°
- Compact lightweight
- Stepless RGBW color mixture
- Masterdimmer
- Internal programs
- Sound-controlled via built-in microphone
- Color change
- Strobe effect with adjustable speed
- Automatic position correction
- Exact positioning via 16 bit PAN/TILT movement resolution
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Control board with LCD for adjusting the DMX-starting address, PAN/TILT Reverse, Reset
- Switch-mode power supply for operation between 100 and 240 volts
- Power connection via P-Con jack and included power cable with safety plug
- Feed-through output allows to power up to 8 devices
- 1 powerful LED 60 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- PAN angle switchable between 540° and 360°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Prism 8-fold; zoom motor driven
- Beam effect
- The device is cooled by cooling fan

Logistic

EAN / GTIN: 4026397594089

Weight: 7,40 kg

Length: 0.31 m

Width: 0.26 m

Height: 0.45 m

- Control via DMX; stand-alone; sound to light via microphone
- Preprogrammed in LED PC-Control 512; Light Captain
- Flicker-free
- With a beam angle of 5° - 47°

Package contents

- 1 x omega bracket

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	90 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	1 x 60 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
Max. TILT movement:	220° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540°, 360° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	0 - 18 Hz
Equipment:	Prism 8-fold; zoom motor driven
DMX channels:	16
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone; sound to light via microphone
Preprogrammed in:	LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	5° - 47°
Beam angle (1/2 peak):	5 - 47°
Beam angle (1/10 peak):	5 - 47°
Illuminance in Lux (lx):	Narrow red (R) 3m: 2276 lx, 6m: 558 lx Narrow green (G) 3m: 4425 lx, 6m: 1098 lx Narrow blue (B) 3m: 906 lx, 6m: 229 lx Narrow cold white (CW) 3m: 6339 lx, 6m: 1582 lx Narrow all 3m: 10534 lx, 6m: 2639 lx Wide red (R) 3m: 64 lx, 6m: 17 lx Wide green (G) 3m: 127 lx, 6m: 35 lx Wide blue (B) 3m: 27 lx, 6m: 8 lx Wide cold white (CW) 3m: 173 lx, 6m: 48 lx Wide all 3m: 296 lx, 6m: 82 lx
Housing color:	Black
Dimensions:	Width: 24,5 cm Depth: 19 cm Height: 37 cm
Weight:	6,40 kg
Legal specifications	

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting