eurolite®

EUROLITE TS-250 Scan

Bright scanner for MSD-lamp



The article is no longer in our assortment.

Features:

- DMX-controlled operation or stand-alone operation with Master/Slave function
- For bright MSD discharge lamp
- Color-wheel with 12 dichroic color filters, 2 bi-color filters and white
- Gobo-wheel with 14 gobos and open
- Manual focus
- Strobe effect with adjustable speed (1-7 flashes/sec.)
- DMX control via every standard DMX controller
- 5 DMX control channels required
- Sound-controlled via built-in microphone
- 5 high-quality stepping-motors
- Suitable EUROLITE controllers: DMX Operator

Technical specifications:

| 230 V AC, 50 Hz |
|-------------------------|
| 460,00 W |
| Width: 27 cm |
| Depth: 55,5 cm |
| Height: 28,5 cm |
| 5 |
| 3-pin XLR |
| via built-in microphone |
| |

Logistic

EAN / GTIN: 4026397217827 Weight: 10,00 kg Length: 0.57 m Width: 0.30 m Heigth: 0.32 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| Flash-rate: | 1-7 Hz |
|-------------------------|--|
| Number of colors: | 14 dichroic + white |
| Number of gobos: | 14 gobos and open |
| PAN-movement: | within 180° |
| TILT-movement: | within 90° |
| Dimensions (L x W x H): | 555 x 270 x 285 mm |
| Weight: | 8 kg |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |
| | |