

EUROLITE LED TMH-19 Moving Head Beam

Moving Head beam with narrow beam angle and 3 W LEDs

Art. No.: 51786051

GTIN: 4026397544534



The article is no longer in our assortment.

Features:

- Equipped with 19 x 3 W LED (4 x red, 5 x green, 6 x blue and 4 x white)
- Compact lightweight
- Narrow beam angle
- Positioning within 540° PAN and 200° TILT
- Stepless RGBW color mixture
- Masterdimmer
- Dimmer speed (step response) adjustable
- Internal program
- Strobe effect with 1-18 flashes per second
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-control via built-in microphone
- Control board with LC display for adjusting the DMX-starting address, PAN/TILT reverse, program, reset
- Switch-mode power supply for operation between 100 and 240 volts
- DMX control via every standard DMX controller
- Preprogrammed in Light´J; LED PC-Control 512
- Flicker-free

Logistic

EAN / GTIN: 4026397544534

Weight: 4,45 kg

Length: 0.28 m

Width: 0.22 m

Height: 0.40 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Preprogrammed in: Light´J; LED PC-Control 512

Projection:	Flicker-free
Illuminance in Lux (lx):	Red (R) 3m: 712 lx, 6m: 246 lx Green (G) 3m: 2199 lx, 6m: 568 lx Blue (B) 3m: 1283 lx, 6m: 324 lx Cold white (CW) 3m: 1878 lx, 6m: 454 lx All 3m: 6365 lx, 6m: 1602 lx
Dimensions:	Width: 20,5 cm Depth: 18 cm Height: 27,5 cm
Power consumption:	60 W
DMX channels:	14
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Flash-rate:	18 Hz
LED type:	Cree 3 W
LED number:	19
Maximum PAN-movement:	540°
Maximum TILT-movement:	200°
Beam angle:	5°
Dimensions (L x W x H):	180 x 205 x 275 mm
Weight:	3.5 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting