# eurolite®

## EUROLITE LED TMH Bar S120 Moving Head Spots

LED lighting system with 4 individually controllable 30 W moving heads, gobo- and color wheel

Art. No.: 51786055 GTIN: 4026397728958









incl. 19% VAT.

#### Features:

- 4 powerful LEDs 30 W COB (chip-on-board)
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution (optional)
- Gobo wheel with static gobos; focus manual; color wheel
- Gobo wheel with static gobos, 7 gobos and open<BR>shake effect
- Color wheel with 7 dichroic filters plus open<BR>half colors selectable, Rainbow effect with adjustable speed
- Strobe effect; beam effect
- Positioning within 540° PAN, 180° TILT
- Exact positioning (16 bit resolution)
- Dimmer electronic
- Flicker-free
- With a beam angle of 13°
- Crossbar with integrated DMX control unit and stand sleeve
- With omega bracket
- 4 digit 7-segment LED display
- Rubber feet
- The device is cooled by temperature-controlled fan
- Mains input and output for power linking up to 8 units
- Preprogrammed in Colorchief; Light J; Light Captain
- For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand Package contents
- 1 x moving light, 1 x user manual, 1 x power cord, 2 x omega bracket, 2 x safety eyelet

#### Logistic

EAN / GTIN: 4026397728958 Weight: 15,00 kg Length: 1.08 m Width: 0.34 m Heigth: 0.26 m

### **Technical specifications:**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	100 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	4 x 30 W COB (chip-on-board)
Max. TILT movement:	180° positioning; exact positioning (16 bit resolution)
Max. PAN movement:	540° positioning; exact positioning (16 bit resolution)
Flash rate:	2 - 14 Hz
Equipment:	Gobo wheel with static gobos; focus manual; color wheel
Color generation:	Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed
Gobos:	Gobo wheel with static gobos, 7 gobos and open Shake effect
DMX channels:	3; 5; 9; 11; 17; 21; 30; 38
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; sound to light via microphone master/slave function; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution (optional)
Preprogrammed in:	Colorchief; Light J; Light Captain
Projection:	Flicker-free
PWM frequency:	11000 Hz
Beam angle:	13°
Beam angle (1/2 peak):	13°
Color temperature:	7300K
Illuminance in Lux (lx):	Cold white (CW) 1m: 8899 lx, 3m: 856 lx, 6m: 205 lx
Housing color:	Black
Attachment system:	2x omega bracket
Display type:	4 digit 7-segment LED display
Transport aid:	Rubber feet
Dimensions:	Width: 100,0 cm Depth: 17,5 cm Height: 28,0 cm

Weight:	13,00 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting