eurolite®

EUROLITE LED TMH-18 Moving Head Beam

LED moving head beam with nine 15 W LEDs

Art. No.: 51786060 GTIN: 4026397561760



The article is no longer in our assortment.

Features:

- DMX-controlled operation or stand-alone operation with Master/Slave function
- Color presets
- Internal programs
- Rainbow effect with adjustable speed
- Stepless RGBW color mixture
- Random strobe effect
- Electronic dimmer
- Control board with graphic LC display for adjusting the DMX-starting address, PAN/TILT reverse, program, reset
- Switch-mode power supply for operation between 100 and 240 volts
- DMX control via every standard DMX controller
- 9 powerful LEDs 15 W high-power 4in1 QCL RGBW (homogenous color mix)
- Exact positioning (16 bit resolution)
- Gobos
- Beam effect
- The device is cooled by cooling fan
- Control via DMX; stand-alone; sound to light via microphone
- Preprogrammed in Light J; LED PC-Control 512
- With a beam angle of 3°

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	125 W









Logistic

EAN / GTIN: 4026397561760 Weight: 6,10 kg Length: 0.41 m Width: 0.32 m Heigth: 0.23 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	9 x 15 W high-power 4in1 QCL RGBW (homogenous color mix)
Max. TILT movement:	200° exact positioning (16 bit resolution)
Max. PAN movement:	540° exact positioning (16 bit resolution)
Flash rate:	0 - 18 Hz
Equipment:	Gobos
DMX channels:	1; 16; 48
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone; sound to light via microphone
Preprogrammed in:	Light J; LED PC-Control 512
Beam angle:	3°
Beam angle (1/2 peak):	3°
Beam angle (1/10 peak):	8°
Illuminance in Lux (Ix):	Red (R) 3m: 2324 lx, 6m: 592 lx Green (G) 3m: 4210 lx, 6m: 1107 lx Blue (B) 3m: 1012 lx, 6m: 277 lx Cold white (CW) 3m: 6714 lx, 6m: 1769 lx All 3m: 12524 lx, 6m: 3277 lx
Housing color:	Black
Dimensions:	Width: 14,5 cm Depth: 26 cm Height: 36 cm
Weight:	5,35 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting