

## EUROLITE LED TMH-S60 Moving Head Spot wh

Compact Moving Head Spot with 60 W LED, gobos, color wheel and white housing

Art. No.: 51786073

GTIN: 4026397713213



**List price: 474.81 €**

incl. 19% VAT.

### Features:

- 3 gobos with heart patterns for exchange included
- 1 powerful LED 60 W COB (chip-on-board) cold white (CW)
- Positioning within 540° PAN and 180° TILT
- Gobo wheel with rotating gobos; Focus manual; color wheel
- Beam effect; Strobe effect
- Color wheel with 7 dichroic filters plus open<BR>half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 7 gobos and open<BR>Slot-in gobo system for easy gobo replacement
- Shake effect
- 4 integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; Sound to light via Microphone; Master/slave function; CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); QuickDMX via USB (optional)
- Flicker-free
- With a beam angle of 12°
- 4 digit 7-segment LED display
- Dimmer electronic
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; Light Captain; Light´J
- Rubber feet
- For application areas such as: Clubs/dancing school; Wedding/gala/events; Stage; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended

### Package contents

### Logistic

EAN / GTIN: 4026397713213

Weight: 3,55 kg

Length: 0.29 m

Width: 0.21 m

Height: 0.27 m

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x safety eyelet, 3 x gobos

## Technical specifications:

|                          |   |
|--------------------------|---|
| Power supply:            | 100-240 V AC, 50/60 Hz  |
| Power consumption:       | 95 W  |
| IP classification:       | IP20  |
| Protection class:        | Protection class I  |
| Power connection:        | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)  |
| Device fuse:             | 5 x 20 mm, T 1,5 A Fuse replaceable   |
| Lamp type:               | LED lamp  |
| LED:                     | 1 x 60 W COB (chip-on-board) cold white (CW)  |
| Color temperature:       | 7700K   |
| Max. TILT movement:      | 180° Positioning  |
| Max. PAN movement:       | 540° Positioning  |
| Equipment:               | Gobo wheel with rotating gobos; Focus manual; color wheel   |
| Color generation:        | Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions   |
| Gobos:                   | Gobo wheel with rotating gobos, 7 gobos and open<br>Outside diameter 13,8mm<br>Image diameter 11mm<br>Slot-in gobo system for easy gobo replacement<br>Shake effect                       |
| DMX channels:            | 10; 12  |
| DMX input:               | 3-pin XLR (M) mounting version  |
| DMX output:              | 3-pin XLR (F) mounting version  |
| Cooling:                 | Cooling fan   |
| Control:                 | Stand-alone; DMX; Sound to light via Microphone; Master/slave function; CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); QuickDMX via USB (optional) |
| Preprogrammed in:        | LED PC-Control 512; EASY SHOW 1; Light Captain; Light J   |
| Projection:              | Flicker-free  |
| Beam angle:              | 12°   |
| Beam angle (1/2 peak):   | 12°   |
| Illuminance in Lux (lx): | Cold white (CW) 1m: 15205 lx, 3m: 1764 lx, 6m: 445 lx   |
| Housing color:           | White   |
| Display type:            | 4 digit 7-segment LED display   |
| Transport aid:           | Rubber feet   |
| Dimensions:              | Width: 17,0 cm<br>Depth: 15,0 cm<br>Height: 24,0 cm   |

|                       |  |
|-----------------------|--|
| Weight:               | 3,15 kg                                      |
| Noise classification: | Class 3 (clearly perceptible sounds)         |
| Legal specifications  |  |
| Special product:      | Not designed for household room illumination |
| Intended use:         | Show effect lighting                         |