

## EUROLITE LED TMH-S90 Moving-Head Spot

LED Moving Head spot with color wheel, static and rotating gobo wheel, prism and focus

Art. No.: 51786075

GTIN: 4026397681499



**List price: 593.81 €**

incl. 19% VAT.

### Features:

- Rotating 3-facet prism with variable speed
- 1 powerful LED 90 W COB (chip-on-board) cold white (CW)
- Positioning within 540° PAN and 200° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Prism 3-fold; gobo wheel with rotating gobos; gobo wheel with static gobos; Focus motor-driven; color wheel
- Color wheel with 7 dichroic filters plus open<BR>half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 6 gobos, 1 multi color gobo and open<BR>shake effect
- Gobo wheel with rotating gobos, 6 gobos and open<BR>shake effect
- Gobos changeable
- Slot-in gobo system for easy gobo replacement
- Integrated show programs
- The device is cooled by cooling fan
- Control via DMX; Sound to light via Microphone; stand-alone; Master/slave function; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
- Flicker-free
- With a beam angle of 12°
- Dimmer electronic
- Preprogrammed in EASY SHOW 1; Light Captain; EASY SHOW 3
- For application areas such as: Clubs/dancing school; Wedding/gala/events; Stage; mobile djs / entertainer
- Application possibility: Standing; suspended

### Package contents

### Logistic

EAN / GTIN: 4026397681499

Weight: 6,85 kg

Length: 0.38 m

Width: 0.32 m

Height: 0.28 m

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x safety eyelet

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	140 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 2 A
Lamp type:	LED lamp
LED:	1 x 90 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	200° Exact positioning (16 bit resolution) Auto position correction (feedback)
Max. PAN movement:	540° Exact positioning (16 bit resolution) Auto position correction (feedback)
Flash rate:	2 - 30 Hz
Equipment:	Prism 3-fold; gobo wheel with rotating gobos; gobo wheel with static gobos; Focus motor-driven; color wheel
Color generation:	Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 6 gobos, 1 multi color gobo and open Shake effect Gobo wheel with rotating gobos, 6 gobos and open Outside diameter 21,8mm Image diameter 16mm Shake effect Gobos changeable Slot-in gobo system for easy gobo replacement
DMX channels:	15
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; Sound to light via Microphone; stand-alone; Master/slave function; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
Preprogrammed in:	EASY SHOW 1; Light Captain; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	12°
Beam angle (1/2 peak):	12°
Illuminance in Lux (lx):	Cold white (CW) 1m: 52772 lx, 3m: 6198 lx, 6m: 1543 lx
Housing color:	Black

Dimensions:	Width: 25,0 cm Depth: 20,5 cm Height: 35,0 cm
Weight:	6,20 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Photobiological safety:	Risk Group 0
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting