

EUROLITE LED TMH-B60 Moving Head Beam

Moving moving head with 60 W COB LED in RGBW

Art. No.: 51786082

GTIN: 4026397710472



List price: 296.31 €

incl. 19% VAT.

Features:

- Compact lightweight
 - 1 powerful LED 60 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
 - Positioning within 540° PAN, 180° TILT
 - Beam effect; strobe effect
 - 4 integrated show programs
 - The device is cooled by cooling fan
 - Control via stand-alone; sound to light via microphone; master/slave function; DMX; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
 - Flicker-free
 - With a beam angle of 2°
 - 4 digit 7-segment LED display
 - Rubber feet
 - Dimmer electronic; Motion macros adjustable
 - Preprogrammed in Light Captain
 - For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer
 - Application possibility: Standing; suspended
- Package contents**
- 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x safety eyelet

Logistic

EAN / GTIN: 4026397710472

Weight: 3,65 kg

Length: 0.29 m

Width: 0.22 m

Height: 0.27 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	60 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, T 1,5 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 60 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
Max. TILT movement:	180° positioning
Max. PAN movement:	540° positioning
DMX channels:	12; 14
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; sound to light via microphone; master/slave function; DMX; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
Preprogrammed in:	Light Captain
Projection:	Flicker-free
Beam angle:	2°
Beam angle (1/2 peak):	2°
Beam angle (1/10 peak):	5°
Illuminance in Lux (lx):	Red (R) 1m: 19079 lx, 3m: 3275 lx, 6m: 838 lx Green (G) 1m: 34129 lx, 3m: 5358 lx, 6m: 1372 lx Blue (B) 1m: 3925 lx, 3m: 1084 lx, 6m: 277 lx Cold white (CW) 1m: 48589 lx, 3m: 8089 lx, 6m: 2048 lx All 3m: 17330 lx, 6m: 4405 lx
Housing color:	Black
Display type:	4 digit 7-segment LED display
Transport aid:	Rubber feet
Dimensions:	Width: 17,5 cm Depth: 15,0 cm Height: 25,0 cm
Weight:	3,25 kg