

EUROLITE LED TSL-1000 Scan

Scanner with 100 W LED, rotating gobos, 3-facet prism, color wheel and motorized focus

Art. No.: 51786122

GTIN: 4026397675320

The article is no longer in our assortment.

Features:

- One high-power 100 W COB LED in cold white
- Positioning within 160° PAN and 50° TILT
- Exact positioning via 16-bit PAN/TILT movement resolution
- Auto, music, master/slave and DMX mode
- Built-in auto and music show programs
- 3-facet prism
- Gobos interchangeable
- Strobe effect with adjustable speed
- Motorized focus
- Electronic dimmer (0-100%) (0-100%) (0-100%) (0-100%) (0-100%)
- Narrow beam angle of 20°
- Control panel with OLED display for easy configuration
- Mains input and output for power linking up to 8 units
- Additional rubber feet protect the device when positioned on the floor
- 1 powerful LED 100 W COB (chip-on-board) cold white (CW)
- Exact positioning (16 bit resolution)
- Focus motor-driven; color wheel; gobo wheel with rotating gobos; prism 3-fold
- Gobo effect
- Color wheel with 8 dichroic filters plus open
rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 7 gobos and open
shake effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; master/slave function; sound to light via microphone
- Preprogrammed in Light Captain; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 20°

Logistic

EAN / GTIN: 4026397675320

Weight: 6,60 kg

Length: 0.49 m

Width: 0.30 m

Height: 0.23 m

- OLED display
- Package contents**
- 1 x device, 1 x user manual, 1 x power cord, 1 x safety eyelet

Technical specifications:

| | |
|--------------------------|-------------------------------------------------------------------------------------------------------------|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 110 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | P-Con (gray), mounting version |
| Fuse: | T 2 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 1 x 100 W COB (chip-on-board) cold white (CW) |
| Max. TILT movement: | 50° exact positioning (16 bit resolution) |
| Max. PAN movement: | 160° exact positioning (16 bit resolution) |
| Flash rate: | 1 - 25 Hz |
| Equipment: | Focus motor-driven; color wheel; gobo wheel with rotating gobos; prism 3-fold |
| Color generation: | Color wheel with 8 dichroic filters plus open Rainbow effect with adjustable speed in both directions |
| Gobos: | Gobo wheel with rotating gobos, 7 gobos and open Shake effect |
| DMX channels: | 10; 15 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | Stand-alone; DMX; master/slave function; sound to light via microphone |
| Preprogrammed in: | Light Captain; EASY SHOW 2; EASY SHOW 3 |
| Projection: | Flicker-free |
| Beam angle: | 20° |
| Beam angle (1/2 peak): | 20° |
| Color temperature: | 8000K |
| Illuminance in Lux (lx): | Cold white (CW) 1m: 35679 lx, 3m: 4265 lx, 6m: 1055 lx |
| Housing color: | Black |
| Display type: | OLED display |
| Dimensions: | Width: 25,1 cm Depth: 14,1 cm Height: 37,7 cm |
| Weight: | 5,80 kg |
| Noise classification: | Class 2 (slight noise) |
| Legal specifications | |

| | |
|------------------|----------------------------------------------|
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |