

EUROLITE LED TSL-1500 Scan

Scanner with 150 W LED, rotating gobos and 4-facet prism, color wheel and motorized focus

Art. No.: 51786127

GTIN: 4026397714456



List price: 712.81 €

incl. 19% VAT.

Features:

- 1 powerful LED 150 W COB (chip-on-board) cold white (CW)
- Positioning within 180° PAN, 70° TILT
- Focus motor-driven; color wheel; gobo wheel with rotating gobos; prism 4-fold rotating
- Dimmer electronic
- Gobo effect; strobe effect
- Color wheel with 8 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 7 gobos and open
shake effect
- Gobos changeable
- Slot-in gobo system for easy gobo replacement
- 9 integrated show programs
- The device is cooled by temperature-controlled fan
- Control via stand-alone; sound to light via microphone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 11°
- OLED display
- Rubber feet
- Preprogrammed in Light Captain
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; rental
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x safety eyelet

Logistic

EAN / GTIN: 4026397714456

Weight: 8,20 kg

Length: 0.60 m

Width: 0.30 m

Height: 0.25 m

Technical specifications:

| | |
|--------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 175 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug |
| Power output: | 1 x P-Con (gray), mounting version |
| Fuse: | 5 x 20 mm, F 5 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 1 x 150 W COB (chip-on-board) cold white (CW) |
| Max. TILT movement: | 70° positioning |
| Max. PAN movement: | 180° |
| Flash rate: | 1 - 30 Hz |
| Equipment: | Focus motor-driven; color wheel; gobo wheel with rotating gobos; prism 4-fold rotating |
| Color generation: | Color wheel with 8 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions |
| Gobos: | Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 19,8mm Image diameter 17mm Shake effect Gobos changeable Slot-in gobo system for easy gobo replacement |
| DMX channels: | 13 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Temperature-controlled fan |
| Control: | Stand-alone; sound to light via microphone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in: | Light Captain |
| Projection: | Flicker-free |
| Beam angle: | 11° |
| Beam angle (1/2 peak): | 11° |
| Color temperature: | 10000K |
| Illuminance in Lux (lx): | Cold white (CW) 3m: 15649 lx, 6m: 4147 lx |
| Housing color: | Black |
| Display type: | OLED display |
| Transport aid: | Rubber feet |
| Dimensions: | Width: 33,5 cm Depth: 16,5 cm Height: 47 cm |

| | |
|----------------------|--|
| Weight: | 7,05 kg |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |