

EUROLITE LED TSL-350 Scan COB

Handy scanner with 60 W COB LED, gobo and color wheel

Art. No.: 51786150 GTIN: 4026397709414











List price: 391.51 €

incl. 19% VAT.

Features:

- Compact design
- 1 powerful LED 60 W COB (chip-on-board) cold white (CW)
- Positioning within TILT
- Color wheel; gobo wheel with rotating gobos; focus manual
- Color wheel with 7 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed
- Gobo wheel with rotating gobos, 7 gobos and open
gobos changeable
- Slot-in gobo system for easy gobo replacement
- Shake effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 11°
- LCD display
- Available in various colors
- Dimmer electronic
- Preprogrammed in Light Captain; Light'J; EASY SHOW 2; EASY SHOW 3
- Rubber feet
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x mounting bracket, 3 x gobos

Logistic

EAN / GTIN: 4026397709414

Weight: 3,60 kg Length: 0.40 m Width: 0.22 m Heigth: 0.21 m

Technical specifications:

| <u> </u> | | |
|---|--|--|
| Power supply: | 100-240 V AC, 50/60 Hz | |
| Power consumption: | 70 W | |
| IP classification: IP20 | | |
| Protection class: | Protection class I | |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) | |
| Fuse: | 5 x 20 mm, T 1,5 A fuse replaceable | |
| Lamp type: LED lamp | | |
| LED type: | 1 x 60 W COB (chip-on-board) cold white (CW) | |
| Equipment: | Color wheel; gobo wheel with rotating gobos; focus manual | |
| Color generation: | Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed | |
| Gobos: Gobo wheel with rotating gobos, 7 gob open Outside diameter 14mm | | |
| | Image diameter 10mm | |
| | Gobos changeable | |
| | Slot-in gobo system for easy gobo replacement Shake effect | |
| DMX channels: | X channels: 10 | |
| DMX input: | 3-pin XLR (M) mounting version | |
| DMX output: | 3-pin XLR (F) mounting version | |
| Cooling: | Cooling fan | |
| Control: Stand-alone; DMX; QuickDMX via USB (or master/slave function; sound to light via microphone; W-DMX by wireless solution v (optional); CRMX by LumenRadio via USB (optional) | | |
| Preprogrammed in: Light Captain; Light ´J; EASY SHOW 2; EAST SHOW 3 | | |
| Projection: Flicker-free | | |
| Beam angle: | 11° | |
| Beam angle (1/2 peak): | m angle (1/2 peak): 11° | |
| Cold white (CW) 1m: 12034 lx, 3m: 1489 lx, 388 lx | | |
| Housing color: | Black | |
| Display type: | LCD display | |
| Transport aid: | Rubber feet | |
| Dimensions: | Width: 16,0 cm | |
| | Depth: 15,0 cm | |
| | Height: 33,0 cm | |
| Weight: | 3,22 kg | |
| Legal specifications | | |
| Special product: Not designed for household room illum | | |

| Intended use: | Show effect lighting |
|---------------|----------------------|
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |