

EUROLITE TMH XB-200 Moving Head Beam

High performance beam for 200 W discharge lamp

Art. No.: 51786800

GTIN: 4026397556438



The article is no longer in our assortment.

Features:

- Very narrow beam angle with 2°
- With electronic ballast
- Color wheel with 13 different dichroic color filters plus white
- Switchable color change (mode 1: only full colors, mode 2: half colors)
- Rainbow effect with adjustable speed
- 8-facet prism
- Frost-filter
- Gobo wheel with 13 static gobos plus open
- With gobo shake function
- Motorized focus
- Strobe effect with adjustable speed
- Random strobe effect
- Dimmer
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- Switch-mode power supply for operation between 100 and 240 volts
- Control board with graphic LC display and encoder for adjusting the DMX-starting address, PAN/TILT reverse, reset, lamp on/off, operating hours
- DMX-controlled operation or stand-alone operation with master/slave function
- For OSD 5 Reflector 200 W discharge lamp
- Power connection via Neutrik PowerCon socket and included power cable
- DMX-control via every standard DMX-controller
- Preprogrammed in LED PC-Control 512

Logistic

EAN / GTIN: 4026397556438

Weight: 14,55 kg

Length: 0.52 m

Width: 0.38 m

Height: 0.38 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Preprogrammed in:	LED PC-Control 512
Dimensions:	Width: 31 cm Depth: 25 cm Height: 38 cm
Power consumption:	250 W
DMX channels:	16
DMX connection:	3-pin XLR
Flash-rate:	1-10 Hz
Color-wheel:	13 dichroic filters plus open
Static gobo-wheel:	13 gobos and open
Maximum PAN-movement:	540°
Maximum TILT-movement:	270°
Beam angle:	2°
Dimensions (L x W x H):	250 x 310 x 380 mm
Weight:	12 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting