

EUROLITE TMH XB-130 Moving-Head-Beam

Bright, extremely narrow beam with Osram Sirius HRI 132 W lamp

Art. No.: 51786810

GTIN: 4026397616644



The article is no longer in our assortment.

Features:

- 11 or 14 DMX channels selectable
- Very narrow beam angle of 1°
- Effect wheel with rotating 8-facet prism
- The prism rotates in both directions and at different speeds
- Motorized focus
- Strobe effect with adjustable speed
- Random strobe effect
- Frost filter
- Dimmer
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- Switch-mode power supply for operation between 100 and 240 Volts
- Control board with LED display for adjusting the DMX-starting address, PAN/TILT reverse, reset, lamp on/off
- PAN-angle switchable between 630° and 540°
- DMX-controlled operation or stand-alone operation with master/slave function
- Software upload by optional accessory via DMX link
- Sound-controlled via built-in microphone
- With Osram Sirius HRI 132 W lamp
- Ready for connection via included IEC power cord with safety power plug
- Feed-through output allows to power up to 8 devices
- DMX-control via any standard DMX-controller
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo wheel with static gobos; prism 8-fold; frost filter; focus motor-driven

Logistic

EAN / GTIN: 4026397616644

Weight: 12,30 kg

Length: 0.53 m

Width: 0.39 m

Height: 0.28 m

- Beam effect
- Color wheel with 14 dichroic filters plus open
rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 17 gobos and open
shake effect
- The device is cooled by temperature-controlled fan
- Control via stand-alone; sound to light via microphone
- Preprogrammed in LED PC-Control 512; Light Captain; Light´J
- With a beam angle of 1°
- OSRAM bulb included

Package contents

- 1 x omega bracket

Technical specifications:

| | |
|------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 170 W |
| IP classification: | IP20 |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x IEC connector (F) mounting version |
| Lamp type: | Discharge lamp |
| Max. TILT movement: | 270° exact positioning (16 bit resolution) auto position correction (feedback) |
| Max. PAN movement: | 540°, 630° exact positioning (16 bit resolution) auto position correction (feedback) |
| Flash rate: | 0 - 20 Hz |
| Equipment: | Gobo wheel with static gobos; prism 8-fold; frost filter; focus motor-driven |
| Color generation: | Color wheel with 14 dichroic filters plus open Rainbow effect with adjustable speed in both directions |
| Gobos: | Gobo wheel with static gobos, 17 gobos and open Shake effect |
| DMX channels: | 11; 14 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Temperature-controlled fan |
| Control: | Stand-alone; sound to light via microphone |
| Preprogrammed in: | LED PC-Control 512; Light Captain; Light´J |
| Beam angle: | 1° |
| Beam angle (1/2 peak): | 1° |
| Housing color: | Black |
| Use of brands: | OSRAM bulb included |
| Dimensions: | Width: 29 cm Depth: 26 cm Height: 40 cm |
| Weight: | 10,65 kg |