

## EUROLITE TMH XB-280 Moving Head Beam

Bright, narrow beam with OSD 10 280W discharge lamp, color wheel, gobos and prisms

Art. No.: 51786825

GTIN: 4026397677171



### Features:

- Equipped with an OSD 10 Reflector 280W discharge lamp
- Positioning within 540° PAN, 270° TILT
- Exact positioning (16 bit resolution)
- Color wheel; focus motor-driven; gobo wheel with static gobos; frost filter; prism 8-fold rotating; prism 24-fold rotating
- Dimmer electronic
- Strobe effect
- Color wheel with 14 dichroic filters plus open<BR>half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 13 gobos und open<BR>shake effect
- The device is cooled by cooling fan
- Control via DMX; stand-alone; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for LED PC-Control 512; Light Captain
- With a beam angle of 2°
- Multicolor LCD display
- For application areas such as: Clubs/dancing school; stage; rental
- Application possibility: Standing; suspended

### Logistic

EAN / GTIN: 4026397677171

Weight: 16,35 kg

Length: 0.60 m

Width: 0.42 m

Height: 0.30 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 385 W

|                         |                                                                                                                                                                                                       |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IP classification:      | IP20                                                                                                                                                                                                  |
| Power connection:       | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug (provided)                                                                                                       |
| Fuse:                   | T 5 A fuse replaceable                                                                                                                                                                                |
| Lamp type:              | Discharge lamp                                                                                                                                                                                        |
| Max. TILT movement:     | 270° exact positioning (16 bit resolution)                                                                                                                                                            |
| Max. PAN movement:      | 540° exact positioning (16 bit resolution)                                                                                                                                                            |
| Flash rate:             | 1 - 18 Hz                                                                                                                                                                                             |
| Equipment:              | Color wheel; focus motor-driven; gobo wheel with<br>static gobos; frost filter; prism 8-fold rotating;<br>prism 24-fold rotating                                                                      |
| Color generation:       | Color wheel with 14 dichroic filters plus open<br>Half colors selectable, Rainbow effect with<br>adjustable speed in both directions                                                                  |
| Gobos:                  | Gobo wheel with static gobos, 13 gobos und open<br>Shake effect                                                                                                                                       |
| DMX channels:           | 16; 19                                                                                                                                                                                                |
| DMX input:              | 3-pin XLR (M) mounting version                                                                                                                                                                        |
| DMX output:             | 3-pin XLR (F) mounting version                                                                                                                                                                        |
| Cooling:                | Cooling fan                                                                                                                                                                                           |
| Control:                | DMX; stand-alone; master/slave function; sound<br>to light via microphone; QuickDMX via USB<br>(optional); W-DMX by wireless solution via USB<br>(optional); CRMX by LumenRadio via USB<br>(optional) |
| Fixtures available for: | LED PC-Control 512; Light Captain                                                                                                                                                                     |
| Beam angle:             | 2°                                                                                                                                                                                                    |
| Beam angle (1/2 peak):  | 2°                                                                                                                                                                                                    |
| Housing color:          | Black                                                                                                                                                                                                 |
| Display type:           | Multicolor LCD display                                                                                                                                                                                |
| Dimensions:             | Width: 30.0 cm<br>Depth: 20.5 cm<br>Height: 50.5 cm                                                                                                                                                   |
| Weight:                 | 14.80 kg                                                                                                                                                                                              |
| Noise classification:   | Class 4 (loud noises)                                                                                                                                                                                 |

## Scope of delivery:

1 x moving light  
1 x user manual  
1 x power cord  
2 x omega bracket