

EUROLITE LED SL-400 DMX Search Light

Follow spot with warm white 300 W LED for medium distances, zoom, CRI >80

Art. No.: 51787320

GTIN: 4026397625059



List price: 2378.81 €

incl. 19% VAT.

Features:

- Manual control via control panel with buttons and faders
 - 1 powerful LED 300 W COB (chip-on-board) warm white (WW)
 - Focus manual; iris stepless
 - The device is cooled by temperature-controlled fan
 - Control via stand-alone; DMX
 - With a beam angle of 7° - 17°
 - Good color rendering index (CRI)
 - With mounting bracket
 - 4 digit 7-segment LED display
 - Direct color temperature selection for 4 preset values
 - Dimmer electronic
 - Strobe effect
 - Suitable for a range of use from 25 to 50 meters
 - Color wheel with 5 dichroic filters plus open half colors selectable
 - Preprogrammed in LED PC-Control 512; Light Captain
 - Built with SEETRONIC connector
 - For application areas such as: Wedding/gala/events; stage; theater; rental
 - Application possibility: Suspended; on stand
- Package contents**
- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x XLR cable, 1 x mounting bracket, 1 x hex key

Logistic

EAN / GTIN: 4026397625059

Weight: 14,35 kg

Length: 0.86 m

Width: 0.33 m

Height: 0.29 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	440 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	1 x 300 W COB (chip-on-board) warm white (WW)
Flash rate:	1 - 20 Hz
Equipment:	Focus manual; iris stepless
Color generation:	Color wheel with 5 dichroic filters plus open Half colors selectable
DMX channels:	6
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX
Preprogrammed in:	LED PC-Control 512; Light Captain
Beam angle:	7° - 17°
Beam angle (1/2 peak):	7 - 13°
Beam angle (1/10 peak):	3 - 17°
Color temperature:	3500K
Color rendering index (CRI):	80 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Use of brands:	Built with SEETRONIC connector
Range of use:	25m - 50m
Dimensions:	Length: 77 cm Width: 27 cm Height: 29 cm
Weight:	12,35 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting