eurolite®

EUROLITE LED SL-600 DMX Search Light

Follow spot with cold white 600 W LED for long distances, zoom, DMX

Art. No.: 51787330 GTIN: 4026397625066









List price: 3449.81 €

incl. 19% VAT.

Features:

- Manual control via movable control panel with buttons and faders
- 1 powerful LED 600 W COB (chip-on-board) cold white (CW)
- Focus manual; iris stepless
- The device is cooled by cooling fan
- Control via DMX
- With a beam angle of 7° 13°
- With mounting bracket
- LCD display
- Direct color temperature selection for 3 preset values
- Dimmer electronic
- Strobe effect
- Suitable for a range of use from 50 to 100 meters
- Color wheel with 7 dichroic filters plus open
half colors selectable
- Preprogrammed in LED PC-Control 512; Light Captain
- Built with SEETRONIC connector
- For application areas such as: Wedding/gala/events; stage; theater; rental
- Application possibility: On stand
- Package contents
- 1 x spotlight, 1 x user manual, 1 x power cord

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	640 W

Logistic

EAN / GTIN: 4026397625066 Weight: 22,50 kg Length: 1.19 m Width: 0.38 m Heigth: 0.40 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	1 x 600 W COB (chip-on-board) cold white (CW)
Flash rate:	1 - 20 Hz
Equipment:	Focus manual; iris stepless
Color generation:	Color wheel with 7 dichroic filters plus open Half colors selectable
DMX channels:	5
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX
Preprogrammed in:	LED PC-Control 512; Light Captain
Beam angle:	7° - 13°
Beam angle (1/2 peak):	7 - 13°
Beam angle (1/10 peak):	7 - 13°
Color temperature:	6500K
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Use of brands:	Built with SEETRONIC connector
Range of use:	50m - 100m
Dimensions:	Length: 105 cm Width: 23 cm Height: 34 cm
Weight:	18,50 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting