

FUTURELIGHT WDR-G5 RX IP Wireless DMX Receiver Outdoor

Weather-proof wireless DMX receiver by Wireless Solution, IP65

Art. No.: 51834027 GTIN: 4026397660036





List price: 284.41 €

incl. 19% VAT.

Description:

Weather-proof wireless DMX receiver by Wireless Solution, IP65

With the weatherproof DMX radio receiver of FUTURELIGHT WDR-G5 you have a wireless receiver for 512 DMX channels, which allows you to operate almost all your devices wirelessly with DMX control. Thanks to the G5 receiver unit incl. antenna from Wireless Solutions you are able to bridge longer distances and leave out annoying cables.

The WDR-G5 is very suitable for use on larger stages or events.

The integrated AFHSS technology ensures interference-free signal transmission in the 2.4 GHz band, which is free of registration and fees worldwide.

The weatherproof die-cast aluminium housing (IP65) is equipped with mounting strips. Thanks to the lockable input socket for mains connection, which withstands almost any weather when closed, the WDR-G5 can also be used for open-air festivals.

The range of the DMX radio receiver is 500 m with visual contact. A simple and quick start-up with only one button is possible thanks to Plug & Play. The integrated LED allows you to easily monitor the operating status.

Features:

- Wireless Solution G5 receiver unit and antenna
- Adaptive frequency hopping ensures interference-free operation in the 2.4 GHz band
- LED for monitoring the operating status
- Lockable power input (IP T-Con)
- Can receive and process up to 512 DMX channels
- Control via W-DMX by wireless solution; plug and play

Logistic

EAN / GTIN: 4026397660036

Weight: 1,45 kg Length: 0.23 m Width: 0.18 m Heigth: 0.13 m

- Operating range up to 500m with line-of-sight
- 2.4 GHz license-free worldwide
- With omega bracket
- Suitable for outdoor use IP65

Package contents

1 x device, 1 x user manual, 1 x power cord, 1 x declaration of conformity, 1 x antenna, 1 x terminating plug (DMX)

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	3 W
IP classification:	IP65
DMX channels:	Input 512
DMX output:	1 x 3-pin XLR (F) mounting version IP
Control:	W-DMX by wireless solution; plug and play
Range:	Range up to 500m with line-of-sight
Frequency band:	2.4 GHz
Modulation:	AFHSS
Attachment system:	Omega bracket
Color:	Grey
Dimensions:	Width: 13,5 cm
	Depth: 10 cm
	Height: 9 cm
Weight:	1,24 kg
· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·