

FUTURELIGHT WDR-CRMX RX IP Wireless DMX Receiver Outdoor

Weather-proof wireless DMX receiver, IP65

Art. No.: 51834032

GTIN: 4026397722550



Features:

- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Can receive and process up to 512 DMX channels
- Lockable power input (IP T-Con)
- Control via CRMX by LumenRadio
- Operating range up to 600m with line-of-sight
- 2.4 GHz license-free worldwide
- With omega bracket
- Suitable for outdoor use IP65

Logistic

EAN / GTIN: 4026397722550

Weight: 1,55 kg

Length: 0.30 m

Width: 0.20 m

Height: 0.14 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	1.6 W
IP classification:	IP65
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
DMX channels:	Input 512
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Control:	CRMX by LumenRadio

Range:	Range up to 600m with line-of-sight
Frequency band:	2.4 GHz
Antenna gain:	5 dBi
Modulation:	GFSK
Attachment system:	Omega bracket
Status LED:	DMX; level meter
Color:	Black
Dimensions:	Length: 17.3 cm Width: 15.6 cm Height: 9.2 cm
Weight:	1.30 kg

Scope of delivery:

- 1 x device
- 1 x user manual
- 1 x power cord
- 1 x omega bracket
- 1 x declaration of conformity