

## **FUTURELIGHT WDS-CRMX Duo TX Wireless DMX Transceiver**

Wireless DMX system 2.4 GHz - two transceivers with CRMX unit in 19" housing

Art. No.: 51834038 GTIN: 4026397726725











List price: 593.81 €

incl. 19% VAT.

### Features:

- Transceiver, to be used as transmitter or receiver
- Control via CRMX by LumenRadio; W-DMX by wireless solution
- Adaptive frequency hopping ensures interference-free operation in the 2.4 GHz band
- Can receive and process up to 1024 DMX channels
- Can transmit up to 1024 DMX channels
- Operating range up to 600m with line-of-sight
- Multicolored LED indicator
- Mains input and output for power linking up to 8 units
- (19") 48.3 cm rack installation 1 U
- Up to 10 transmitters can be operated in parallel without interference

#### Package contents

1 x device, 1 x user manual, 1 x power cord, 1 x declaration of conformity

## **Technical specifications:**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	3 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (gray), mounting version

# Logistic

EAN / GTIN: 4026397726725

Weight: 1,80 kg Length: 0.50 m Width: 0.25 m Heigth: 0.10 m

Device fuse:	T 1 A fuse serviceable
DMX channels:	Input 1024
	Output 1024
DMX input:	2 x 3-pin XLR (M) mounting version
	2 x 5-pin XLR (M) mounting version
DMX output:	2 x 3-pin XLR (F) mounting version
	2 x 5-pin XLR (F) mounting version
Control:	CRMX by LumenRadio; W-DMX by wireless solution
Range:	Range up to 600m with line-of-sight
Carrier frequency:	2,4 GHz
Parallel mode:	Max. 10 transmitter
Antenna gain:	3 dBi
Modulation:	GFSK
Status LED:	DMX, level meter, power
Color:	Black
Housing design:	(19") 48.3 cm rack installation 1 U
Dimensions:	Length: 48,3 cm
	Depth: 14,0 cm
	Height: 44 cm
Weight:	1,33 kg