

## FUTURELIGHT ODD-L Outdoor dome

The perfect protection

Art. No.: 51837220

GTIN: 4026397250947



**The article is no longer in our assortment.**

### Description:

Let's go outside! You want to use moving-heads outdoors and keep them safe from any weather influences? Then we recommend the ODD. This outdoor dome has a base of metal where a moving head, for example, is placed. Now a self-inflatable protection dome is put over the lighting effect. It is an invisible, because transparent, splash-proofed construction for the perfect outdoor-light delight. By the way, the ODD can also be mounted headfirst. Thanks to also delivered air hoses, the fans will not get flooded with water.

### Logistic

EAN / GTIN: 4026397250947

Weight: 31,30 kg

Length: 0.83 m

Width: 0.68 m

Height: 0.28 m

### Features:

- Weather-proof housing for Moving-Heads, scanners, lighting effects etc.
- The device which is to be protected is easily placed in the ODD or installed via the mounting bracket
- Use either standing on the feet or installed in the truss via Omega-Clamps
- Headfirst installation via mounting bracket and air tubes
- Self-inflatable protection dome
- Invisible because transparent
- Splash-proof construction for outdoor use
- With integrated pressure sensor for automatic cutoff in case of dome deflation

### Technical specifications:

Power supply: 230 V AC, 50 Hz

Power consumption: 1700 W

|   |   |
|---|---|
| IP classification:                        | IP44  |
| Output current:                           | Max. 6,5 A                                      |
| Dimensions:                               | Width: 63 cm<br>Depth: 63 cm<br>Height: 22,5 cm |
| Weight:                                   | 27,70 kg  |
| Max. power output (safety power outlet):  | 1500 W  |
| Max. total current (safety power outlet): | 6.5 A   |
| Protection grade:                         | IP44  |
| DMX connection:                           | 3-pin XLR                                       |
| Dimensions (L x W x H):                   | 630 x 630 x 225 mm                              |
| Height with inflated cover:               | 1300 mm   |
| Max. tearing load:                        | 45 kg   |
| Max. pressing load:                       | 45 kg   |