

FUTURELIGHT IP PLB-420 Moving Head beam

Weather-proof beam moving-head (IP65) with 420 W discharge lamp & CRMX wireless receiver

Art. No.: 51838830

GTIN: 4026397704969

**List price: on demand €**

incl. 19% VAT.

Features:

- Light source: USHIO NSL 420W discharge lamp (2000 hrs)
- Bidirectional rotating honeycomb prism, 8-facet prism with variable speed, combinable for multi-facet effects
- 16-bit technology for dimmer, focus and PAN/TILT positioning
- Automatic position correction
- Strobe effect with adjustable speed, random strobe effect and pulse effect
- User-definable scenes
- Software updates via DMX or USB
- Color wheel 13 dichroitic colors and open
Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 14 gobos und open
shake effect
- Integrated Showprograms
- Can be operated in 18 CH mode
- The device is cooled by temperature-controlled fan
- Controlling by stand-alone; Master/slave function; DMX; RDM; CRMX by LumenRadio built-in; ArtNet; sACN; Sound to light via Microphone possible
- With a beam angle of 1°
- With Omega holder
- Multicolor LCD display, battery-powered for easy controlling
- Suitable for outdoor use

Logistic

EAN / GTIN: 4026397704969

Weight: 44,50 kg

Length: 0.86 m

Width: 0.56 m

Height: 0.46 m

Bulky product

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	420 W
IP classification:	IP65
Protection class:	Class I
Power connection:	Mains input via IP T-Con (M) power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, T 4 A
Lamp type:	Discharge lamp
Max. TILT movement:	Exact positioning (16 bit resolution) 265° Auto position correction (feedback)
Max. PAN movement:	Exact positioning (16 bit resolution) 540° Auto position correction (feedback)
Equipment:	Prism Honeycomb; Prism 8-fold; Focus motor-driven; gobo wheel with static gobos; color wheel
Color generation:	Color wheel 13 dichroitic colors and open
Gobos:	Gobo wheel with static gobos, 14 gobos und open Shake effect
DMX channels:	18
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Temperature-controlled fan
Control:	Stand-alone; Master/slave function; DMX; RDM; CRMX by LumenRadio built-in; ArtNet; sACN; Sound to light via Microphone possible
Beam angle:	1°
Beam angle (1/2 peak):	1°
Housing color:	Black
Attachment system:	2x Omega holder
Display type:	Multicolor LCD display battery-powered
Connections:	2 x RJ-45 (F) mounting version
Dimensions:	Width: 45 cm Depth: 35 cm Height: 76 cm
Weight:	39,50 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting