

# **FUTURELIGHT PLS-5R Moving-Head**

Brilliant multifunction moving head with Philips Platinum 5R lamp

Art. No.: 51838910 GTIN: 4026397437881



## The article is no longer in our assortment.

### Features:

- Double lamp lifetime with half power input and smaller dimensions compared to a 575 W lamp
- Supports RDM (Remote Device Management)
- Color-wheel with 5 different, dichroic color filters and white and additionally with CTO and CTB correction filters and UV filter
- Switchable color change (mode 1: only full colors, mode 2: color-change at every position)
- Rainbow effect with adjustable speed in both directions
- Gobo-wheel with 14 static metal gobos plus open
- Gobo-wheel with 8 rotating gobos plus open
- Slot-in gobo-system for exchanging gobos without tools
- With gobo-shake function
- Rotating 3-facet prism
- Macro-function for rotating gobos/rotating prism combinations
- Steplessly adjustable iris
- Motorized focus
- Graphic LCD-display
- Strobe effect with 1-13 flashes per second
- Random strobe effect
- Stepless frost-filter for fading the projections in or out
- Mechanic dimmer
- Exact positioning via 16 bit resolution: color-wheel, gobo indexing, prism indexing, focus, dimmer, iris and PAN/TILT movement
- Automatic position correction
- ESDC function (Easy Service Data Check) with battery-buffered control board for operation time readouts etc.
- Control board with LCD display and touch keyboard for adjusting the DMX-starting address, PAN/TILT reverse, program, reset, lamp on/off, operating hours

## Logistic

EAN / GTIN: 4026397437881

Weight: 20,50 kg Length: 0.64 m Width: 0.42 m Heigth: 0.45 m

- PAN-angle switchable between 630° and 540°
- DMX-controlled operation or stand-alone operation with master/slave function
- 7 built-in programs can be called up via DMX-controller
- 56 preprogrammed scenes in Program Run for stand alone operation
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- Software upload by optional accessory via DMX link
- Sound-controlled via built-in microphone
- With PHILIPS MSD Platinum 5R discharge lamp
- The integral mounting plate on the bottom of the device enables a permanent installation even without omega clamps, e.g. on the ceiling
- Power connection via Neutrik PowerCon jack and included power cable
- DMX-control via every standard DMX-controller

#### device

- Cordless, flexible and versatile

### Package contents

- 1 x device

## **Technical specifications:**

Power supply:	230 V AC, 50 Hz
Power consumption:	300,00 W
Weight:	17,60 kg
Device	
Battery pack type:	1 x lithium ion 3,7 V, 1,85 Wh
DMX channels:	15/17/24
DMX connection:	5-pin and 3-pin XLR
Flash-rate:	13 Hz
Color-wheel:	5 dichroic plus white, CTO and CTB correction filters, UV filter
Static gobo wheel:	14 gobos and open
Rotating gobo wheel:	8 gobos and open
Outside diameter of the gobos:	14 mm
Image diameter of the gobos:	7 mm
Maximum PAN-movement 630°:	in 2 s
Maximum TILT-movement 270°:	in 1.5 s
Beam angle:	16°
Length of base (including handles):	362 mm
Width of yoke:	335 mm
Height (head horizontal):	480 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting