

## FUTURELIGHT PLB-130 Moving Head

High performance beam with Osram Sirius HRI 132 W lamp

Art. No.: 51838945

GTIN: 4026397503050



**The article is no longer in our assortment.**

### Features:

- Parallel beam
- Effect wheel with rotating 8-facet prism
- The prism rotate in both directions and at different speeds
- Motorized focus
- Strobe effect with adjustable speed
- Random strobe effect
- Electronic dimmer (0-100%)
- Exact positioning via 16-bit PAN/TILT movement resolution
- Automatic position correction
- Control panel with LC display for easy configuration
- PAN angle switchable between 630° and 540°
- Stand-alone, master/slave and DMX mode
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- Software upload by optional accessories via DMX link
- With Osram Sirius HRI 132 W lamp
- Gobos
- Gobo effect
- Color wheel with 14 dichroic filters plus open<BR>rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 17 gobos and open<BR>shake effect
- The device is cooled by temperature-controlled fan
- Control via RDM; DMX; stand-alone; sound to light via microphone
- Preprogrammed in LED PC-Control 512; Light Captain; Light 'J
- With a beam angle of 2°

### Logistic

EAN / GTIN: 4026397503050

Weight: 13,20 kg

Length: 0.51 m

Width: 0.38 m

Heigh: 0.27 m

**Package contents**

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x XLR cable

**Technical specifications:**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	190 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Fuse:	T 3,15 A fuse replaceable
Lamp type:	Discharge lamp
Max. TILT movement:	265° positioning
Max. PAN movement:	630° positioning
Flash rate:	1 - 20 Hz
Equipment:	Gobos
Color generation:	Color wheel with 14 dichroic filters plus open Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 17 gobos and open Shake effect
DMX channels:	10; 12; 13; 16
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	RDM; DMX; stand-alone; sound to light via microphone
Preprogrammed in:	LED PC-Control 512; Light Captain; Light´J
Beam angle:	2°
Beam angle (1/2 peak):	2°
Housing color:	Black
Dimensions:	Width: 25 cm Depth: 30 cm Height: 40 cm
Weight:	11,70 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Legal specifications	
Energy efficiency class (A++ - E):	G