

FUTURELIGHT PLB-230 Moving Head

High performance beam with Osram Sirius HRI 230 W lamp and LED ring with RGB color mixture

Art. No.: 51838951

GTIN: 4026397484120



List price: 2021.81 €

incl. 19% VAT.

Features:

- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- Effect wheel with rotating 3-facet prism and 8-facet prism and frost filter
- Strobe effect with adjustable speed
- Random strobe effect
- Electronic dimmer (0-100%)
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- PAN-angle switchable between 630° and 540°
- Number of scenes in Program Run can be changed individually
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Software upload by optional accessories via DMX link
- With already installed Osram Sirius HRI 230 W lamp
- 12 powerful LEDs 3 W 3in1 TCL RGB
- Color wheel 14 dichroic filters plus open
Rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 8 gobos and open
shake effect
- Gobos changeable
- Slot-in gobo system for exchanging gobos without tools
- Can be operated in 17; 19; 21; 24 CH mode
- The device is cooled by temperature-controlled fan
- Controlling by RDM; DMX; stand-alone; W-DMX by wireless solution built-in; Sound to light via Microphone
- Preprogrammed in LED PC-Control 512
- Effect: Gobo effect
- With a beam angle of 1,3°

Logistic

EAN / GTIN: 4026397484120
 Weight: 18,10 kg
 Length: 0.61 m
 Width: 0.44 m
 Height: 0.36 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	325,00 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug
Lamp type:	Discharge lamp
LED:	12 x 3 W 3in1 TCL RGB
Max. TILT movement:	Exact positioning (16 bit resolution) 270° Auto position correction (feedback)
Max. PAN movement:	Exact positioning (16 bit resolution) 540° Positioning switchable to 630° Auto position correction (feedback)
Flash rate:	0 - 20 Hz
Equipment:	Gobo wheel with rotating gobos; Focus motor-driven
Color generation:	Color wheel 14 dichroic filters plus open
Gobos:	Gobo wheel with rotating gobos, 8 gobos and open Outside diameter 14mm Image diameter 6mm Shake effect Gobos changeable Slot-in gobo system for exchanging gobos without tools
DMX channels:	17; 19; 21; 24
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	RDM; DMX; stand-alone; W-DMX by wireless solution built-in; Sound to light via Microphone; LED PC-Control 512
Beam angle:	1,3°
Beam angle (1/2 peak):	1,3°
Housing color:	Black
Carrier frequency:	2,4 GHz
Dimensions:	Width: 25 cm Depth: 42,4 cm Height: 34,3 cm
Weight:	16,20 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting
Lamp:	1 x conventional with EEI C included