

FUTURELIGHT Color Wave LED Moving Bar

Moving Head with two tiltable LED bars and colorful beams

Art. No.: 51839005

GTIN: 4026397513141



The article is no longer in our assortment.

Features:

- TILT movement for each LED bar separately and steplessly adjustable
- Individual control of each LED
- Built-in programs
- Color presets
- Shutter sequences
- Electronic dimmer (0-100%)
- Automatic position correction
- Exact positioning via 16 bit PAN/TILT movement resolution
- PAN angle switchable between 540° and 630°
- Random strobe effect
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- 6 powerful LEDs 10 W high-power 4in1 QCL RGBW
- Can be operated in 18; 17 CH mode
- The device is cooled by temperature-controlled fan
- Controlling by RDM; DMX; stand-alone; Sound to light via Microphone
- Preprogrammed in LED PC-Control 512
- Effect: Fan effect
- With a beam angle of 2,5°

Logistic

EAN / GTIN: 4026397513141

Weight: 12,10 kg

Length: 0.54 m

Width: 0.40 m

Height: 0.34 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	120 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED:	6 x 10 W high-power 4in1 QCL RGBW
Max. TILT movement:	Exact positioning (16 bit resolution) 240° Auto position correction (feedback)
Max. PAN movement:	Exact positioning (16 bit resolution) 540° Positioning switchable to 630° Auto position correction (feedback)
Flash rate:	0 - 20 Hz
DMX channels:	18; 17
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	RDM; DMX; stand-alone; Sound to light via Microphone; LED PC-Control 512
Beam angle:	2,5°
Beam angle (1/2 peak):	2,5°
Illuminance in Lux (lx):	Red (R) 3m: 1713 lx, 6m: 655 lx Green (G) 3m: 2074 lx, 6m: 868 lx Blue (B) 3m: 861 lx, 6m: 217 lx Cold white (CW) 3m: 4037 lx, 6m: 452 lx
Housing color:	Black
Dimensions:	Width: 46,8 cm Depth: 25 cm Height: 32,5 cm
Weight:	10,30 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting