

FUTURELIGHT DSC-40 LED-Scan

PRO LED scanner with LUMINUS SST-90 LED











The article is no longer in our assortment.

Features:

- 12 or 14 DMX channels selectable for numerous applications
- Color-wheel with 7 different, dichroic color filters, UV filter and white
- Switchable color change (mode 1: only full colors, mode 2: color-change at every position)
- Rainbow effect with adjustable speed in both directions
- Slot-in gobo system for exchanging gobos without tools
- Gobo wheel with 7 rotating gobos plus open
- All gobos can be interchanged
- With gobo shake function
- Effect wheel with rotating 3-facet prism and 3D prism
- Macro function for rotating gobos/rotating prism combinations
- Frost filter
- Motorized focus
- Dimmer
- Strobe effect with 1-13 flashes per second via shutter
- Random strobe effect
- Exact positioning via 16 bit PAN/TILT movement resolution
- Controlboard with 4-digit display and foil-keyboard for adjusting the DMX starting address, PAN/TILT Reverse, Program, Reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 7 built-in programs can be called up via DMX controller
- 48 preprogrammed scenes in Program Run for stand-alone operation
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the control board or via an external controller and loaded into the memory
- Software-upload by optional accessory via DMX link
- Sound-controlled via built-in microphone

Logistic

EAN / GTIN: 4026397447774 Weight: 10,00 kg Length: 0.68 m Width: 0.38 m Heigth: 0.35 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- DMX control via every standard DMX controller
- 1 powerful LED
- Gobo wheel with rotating gobos
- Gobo wheel with rotating gobos, 7 gobos and open
gobos changeable
- Control via sound to light via microphone; RDM

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	115 W
LED type:	1
Max. TILT movement:	45° positioning
Max. PAN movement:	180° positioning
Flash rate:	1 - 13 Hz
Equipment:	Gobo wheel with rotating gobos
Gobos:	Gobo wheel with rotating gobos, 7 gobos and open
	Outside diameter 27mm
	Image diameter 22mm Gobos changeable
DMX channels:	12
Control:	Sound to light via microphone; RDM
Beam angle (1/2 peak):	12°
Color:	Black
Dimensions:	Width: 30 cm
	Depth: 57 cm
	Height: 30 cm
Weight:	7,90 kg
DMX channels:	12/14
DMX connection:	3-pin XLR
Flash-rate:	13 Hz
Sound-control:	via built-in microphone
LED type:	LUMINUS SST-90
LED number:	1
Color-wheel:	7 dichroic filters, UV filter and open
Rotating gobo-wheel:	7 gobos and open
Outside diameter of the gobos:	27 mm
Image diameter of the gobos:	22 mm
Maximum PAN-movement:	180°
Maximum TILT-movement:	45°
Beam angle:	12°
Dimensions (L x W x H):	570 x 300 x 300 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting