

## FUTURELIGHT EYE-19 HCL Zoom LED Moving Head Wash

PRO washlight with 6in1 COB LEDs, color rendering index (CRI) >90 and very large zoom range

Art. No.: 51841313

GTIN: 4026397659658

**The article is no longer in our assortment.**

### Features:

- Compact design
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- 19 powerful LEDs 17 W high-power 6in1 HCL RGBALC (homogenous color mix)<BR>2 segments controlled separately
- Positioning within 630° PAN, 265° TILT
- Auto position correction (feedback)
- Zoom motor driven
- Integrated show programs
- The device is cooled by temperature-controlled fan
- Control via DMX; RDM; master/slave function; sound to light via microphone; W-DMX by wireless solution upgradeable
- Flicker-free
- With a beam angle of 2° - 36°
- Very high color rendering index (CRI)
- For application areas such as: Theater; clubs/dancing school; Trade fair and shop fitting; installation; stage; concerts/FoH's; rental
- Exact 16 bit resolution at Dimmer
- Pulse-width modulation variable; color selection; color blend stepless
- Strobe effect
- Preprogrammed in Light'J; LED PC-Control 512; Light Captain
- Very quiet working noise
- Mains input and output for power linking up to 8 units

### Package contents

### Logistic

EAN / GTIN: 4026397659658

Weight: 16,15 kg

Length: 0.52 m

Width: 0.42 m

Height: 0.33 m

- 1 x moving light, 1 x user manual, 1 x power cord, 2 x omega bracket, 1 x XLR cable, 1 x declaration of conformity

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	300 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED type:	19 x 17 W high-power 6in1 HCL RGBALC (homogenous color mix)
Max. TILT movement:	265° positioning auto position correction (feedback)
Max. PAN movement:	630° auto position correction (feedback)
Flash rate:	1 - 18 Hz
Equipment:	Zoom motor driven
DMX channels:	16; 19; 20; 33
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	DMX; RDM; master/slave function; sound to light via microphone; W-DMX by wireless solution upgradeable
Preprogrammed in:	Light´J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	2° - 36°
Beam angle (1/2 peak):	2 - 15°
Beam angle (1/10 peak):	7 - 36°
Color rendering index (CRI):	90 Ra
Illuminance in Lux (lx):	Narrow red (R) 3m: 2300 lx, 6m: 617 lx Narrow green (G) 3m: 5241 lx, 6m: 1329 lx Narrow blue (B) 3m: 1118 lx, 6m: 285 lx Narrow amber (A) 3m: 10211 lx, 6m: 2665 lx Narrow lime 3m: 16696 lx, 6m: 4389 lx Narrow cyan 3m: 2453 lx, 6m: 652 lx Narrow all 3m: 34599 lx, 6m: 9025 lx Wide red (R) 3m: 201 lx, 6m: 57 lx Wide green (G) 3m: 469 lx, 6m: 132 lx Wide blue (B) 3m: 105 lx, 6m: 30 lx Wide amber (A) 3m: 877 lx, 6m: 245 lx Wide lime 3m: 1384 lx, 6m: 387 lx Wide cyan 3m: 228 lx, 6m: 64 lx Wide all 3m: 2969 lx, 6m: 827 lx
Housing color:	Black

Dimensions:	Width: 25,0 cm
	Depth: 34,2 cm
	Height: 45,8 cm
Weight:	14,40 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting