

FUTURELIGHT EYE-19 HCL Zoom LED Moving Head Wash

PRO washlight with 6in1 COB LEDs, color rendering index (CRI) >90 and very large zoom range

Art. No.: 51841313

GTIN: 4026397659658



List price: 2378.81 €

incl. 19% VAT.

Features:

- Equipped with 19 x 17 W 6in1 LED in R/G/B/Lime/Amber/Cyan
- Variable PWM frequency (pulse-width modulation)
- Optional W-DMX receiver for wireless DMX Control
- Compact design
- 2 different LED segments, which can be controlled individually via DMX
- Exact positioning via 16-bit PAN/TILT movement resolution
- 16-bit technology for high-resolution dimming
- Motorized zoom with 2-36° beam angle
- Color presets
- Variable color temperature
- Built-in programs
- Stepless color blend
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- ESDC function (Easy Service Data Check) with battery-buffered control board for operation time readouts etc. (the Li-Ion battery 3.7V, AAA, 10440 is not included)
- Control panel with LC display for easy configuration
- Stand-alone, master/slave and DMX mode
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- Mains input and output for power linking up to 8 units
- LED: 19 x high-power 17 W 6in1 HCL RGBALC (homogenous color mix)

Logistic

EAN / GTIN: 4026397659658
 Weight: 16,15 kg
 Length: 0.52 m
 Width: 0.42 m
 Height: 0.33 m

- Can be operated in 16; 19; 20; 33 CH mode
- The device is cooled by temperature-controlled fan
- Controlling by DMX; W-DMX by wireless solution upgradeable; RDM; Master/slave function; Sound to light via Microphone
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- Flicker-free projection
- Very high color rendering index (CRI)

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	300 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED:	19 x high-power 17 W 6in1 HCL RGBALC (homogenous color mix)
Max. TILT movement:	265° Auto position correction (feedback)
Max. PAN movement:	630° Auto position correction (feedback)
Flash rate:	1 - 18 Hz
Equipment:	Zoom motor-driven
DMX channels:	16; 19; 20; 33
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	DMX; W-DMX by wireless solution upgradeable; RDM; Master/slave function; Sound to light via Microphone; Light´J; LED PC-Control 512; Light Captain
Beam angle:	2 - 36°
Beam angle (1/2 peak):	2 - 15°
Beam angle (1/10 peak):	7 - 36°
Color rendering index (CRI) more than:	90 Ra
Illuminance in Lux (lx):	Narrow red (R) 3m: 2300 lx, 6m: 617 lx Narrow green (G) 3m: 5241 lx, 6m: 1329 lx Narrow blue (B) 3m: 1118 lx, 6m: 285 lx Narrow amber (A) 3m: 10211 lx, 6m: 2665 lx Narrow Lime 3m: 16696 lx, 6m: 4389 lx Narrow cyan 3m: 2453 lx, 6m: 652 lx Narrow all 3m: 34599 lx, 6m: 9025 lx Wide red (R) 3m: 201 lx, 6m: 57 lx Wide green (G) 3m: 469 lx, 6m: 132 lx Wide blue (B) 3m: 105 lx, 6m: 30 lx Wide amber (A) 3m: 877 lx, 6m: 245 lx Wide Lime 3m: 1384 lx, 6m: 387 lx Wide cyan 3m: 228 lx, 6m: 64 lx Wide all 3m: 2969 lx, 6m: 827 lx

Housing color:	Black
Dimensions:	Width: 25,0 cm Depth: 34,2 cm Height: 45,8 cm
Weight:	14,40 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting