

# FUTURELIGHT EYE-36 RGB Moving-Head Wash

LED moving head washlight

# The article is no longer in our assortment.

### **Description:**

#### It's time for a revolution!

LEDs have revolutionized the illumination industry. In the meantime, they have reached almost every area and replace the well-tried illuminants or at least compete heavily with them. Moving heads have also got into the focus of diodes. The FUTURELIGHT EYE-36 MK2 sets an appropriate example. This head moving washlight is equipped with 36 LEDs (1 watt; 12 x red, 12 x blue, 12 x green), weighs less than its conventional competitors and thus is easy to transport. Beside the well-known and undeniable advantages of LEDs, such as the low power consumption and the low maintenance, the powerful EYE-36 offers a specialty. Because the radiation angle, normally 25°, can be changed via an optional, exchangeable lense module from 38° to 15°. Not only due to the different angles, the EYE-36 is a competitor which should be taken seriously.

### Features:

- Equipped with 36 x 1 W LEDs: 12 x red, 12 x blue, 12 x green
- Different radiation angles (from approx. 38° to approx. 15°) possible via optional, exchangeable lens module
- Stepless RGB color changing
- Masterdimmer
- Strobe effect
- **Built-in sequences**
- Compact housing
- Positioning within 540° PAN and 270° TILT
- Vector and tracking mode
- Advantages of LED technology: long life, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation

#### Logistic

EAN / GTIN: 4026397355277 Weight: 13,00 kg Length: 0.41 m Width: 0.42 m Heiath: 0.46 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

















GTIN: 4026397355277

- Control board with 4-digit display for adjusting the DMX-starting address, PAN/TILT-Reverse, Program, Reset
- DMX control via every standard DMX controller

## **Technical specifications:**

Power supply:	230 V AC, 50 Hz
Power consumption:	160 W
Max. TILT movement:	270° positioning
Max. PAN movement:	540° positioning
Flash rate:	1 - 18 Hz
DMX channels:	12
Beam angle (1/2 peak):	38°
Dimensions:	Length: 33,50 cm
Weight:	11,05 kg
DMX channels:	12
DMX connection:	3-pin XLR
Flash-rate:	18 Hz
LED number:	36
Beam angle:	38°
Length of base:	335 mm
Width of yoke:	305 mm
Height (head horizontal):	375 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting