

FUTURELIGHT LIS-69 RGB LED-Head effect

Versatile LED Head Effect

Art. No.: 51841335

GTIN: 4026397310382



The article is no longer in our assortment.

Description:

The so far undiscovered country!

Just like CDs experience a keen competition by the innovative MP3 and MP4 formats, conventional illuminants are confronted with a huge armada of LEDs. It is the immense diversity, that characterizes the diodes and now they don't even stop for moving heads. Our LIS-69 is the best example sample. Because in some respects it combines the advantages of a MAT-64 and those of a moving head. The 69 LEDs shine very powerful and project pictures, patterns as well as animations and to some extent, operate like a laser show. Moreover, the device turns to the desired direction and thus gives much leeway to illumination possibilities. Now we add a bit of smoke and voilà, the dish can be served. Just try it, it may be your favorite one.

Logistic

EAN / GTIN: 4026397310382

Weight: 15,20 kg

Length: 0.58 m

Width: 0.45 m

Height: 0.46 m

Features:

- Equipped with 69 LEDs: 24 x red, 21 x green, 24 x blue
- Creates 24 various RGB patterns (gobos) via LED matrix
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 48 preprogrammed scenes in Program Run for stand-alone operation
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- 8 built-in programs can be called up via DMX controller
- Sound-controlled via built-in microphone
- Advantages of LED technology: long life, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation
- Positioning within 360° Pan and 265° Tilt

- Control board with 4-digit display and foil-keyboard for adjusting the DMX-starting address, Pan/Tilt Reverse, Program, Reset
- DMX control via every standard DMX controller

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	35,00 W
DMX channels:	9
DMX connection:	3-pin XLR
LED number:	69
LED type:	5 mm
Beam angle:	28°
Maximum PAN-movement 360°:	in 2.0 s
Maximum TILT-movement 265°:	in 1.5 s
Length of base:	380 mm
Width of yoke:	330 mm
Height (head horizontal):	450 mm
Weight:	10.5 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting