

FUTURELIGHT EYE-190 Zoom LED Moving-Head Wash

Moving Head wash with 10 W 4in1 LEDs

Art. No.: 51841344 GTIN: 4026397474060



The article is no longer in our assortment.

Features:

- Equipped with 19 quadcolor LEDs in the colors RGBW (Osram)
- With integrated wireless receiver for WDMX operation (Wireless Solution made in Sweden)
- Supports RDM (Remote Device Management)
- 20, 32 or 42 DMX channels selectable
- Exact positioning via 16-bit Pan/Tilt movement resolution
- PAN angle switchable between 630° and 540°
- Stepless RGBW color changing
- 19 LEDs in 3 LED groups independently controllable
- Programmable color change speed and strobe effect
- Strobe effect with 1-18 flashes per second
- Random strobe effect
- Motorized zoom with 13°-27° beam angle
- Masterdimmer
- Color presets
- Color macros
- Chase patterns
- Automatic position correction
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-controlled via built-in microphone
- ESDC function (Easy Service Data Check) with battery-buffered Control Board for operation time readouts etc.
- Control board with graphic LCD display and touch keyboard for adjusting the DMX-starting address, PAN/TILT reverse, program, reset, operating hours
- RDMX (Remote DMX Addressing): DMX address setting via controller possible
- 7 built-in programs can be called up via DMX controller
- 56 preprogrammed scenes in Program Run for stand-alone operation

Logistic

EAN / GTIN: 4026397474060 Weight: 18,15 kg Length: 0.58 m Width: 0.45 m Heigth: 0.36 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- Software upload by optional accessory via DMX link
- Switch-mode power supply
- Automatic power supply adaption between 100 and 240 Volts without power selector
- Power connection via Neutrik PowerCon jack and included power cable
- DMX control via every standard DMX controller device
- Cordless, flexible and versatile
- Package contents
- 1 x device

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	295,00 W
Dimensions:	Width: 37 cm
	Depth: 24,5 cm
	Height: 49,4 cm
Device	
Battery pack type:	1 x lithium ion 3,7 V,
DMX channels:	20/32/42
DMX connection:	5-pin and 3-pin XLR
Sound-control:	via built-in microphone
Wireless signal transmission:	2.4 GHz (ISM)
Flash-rate:	18 Hz
LED type:	10 W QCL
LED number:	19
Maximum PAN-movement:	630°
Maximum TILT-movement:	265°
Beam angle:	13° - 27°
Dimensions (L x W x H):	370 x 245 x 494 mm
Weight:	15 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting