

FUTURELIGHT Stage Pixel Bar 5

Bar with narrow beam 5 x 15 W RGBW LED and frost plate

Art. No.: 51841358 GTIN: 4026397561081











The article is no longer in our assortment.

Features:

- Additional frost filter provides a wide, soft and homogeneous light
- For use via appropriate lighting control software supporting Art-Net
- 5 powerful LEDs 15 W high-power 4in1 QCL RGBW (homogenous color mix)
 LEDs controlled separately
- Color change adjustable; Dimmer speed (step response) adjustable
- Strobe effect
- Integrated show programs
- Direct color selection
- Control via Art-Net; stand-alone; DMX; sound to light via microphone; RDM
- Preprogrammed in Light'J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 4°
- With mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; rental
- Application possibility: Standing; suspended; on stand

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	100 W
IP classification:	IP20

Logistic

EAN / GTIN: 4026397561081

Weight: 7,20 kg Length: 0.54 m Width: 0.27 m Heigth: 0.23 m

LED type: LED type: 5 x 15 W high-power 4in1 QCL RGBW (homogenous color mix) Flash rate: 0 - 18 Hz DMX channels: 4; 6; 8; 20; 24 DMX input: 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version 1 x 5-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version Protocol: Art-Net 3 via 2x RJ-45 etherCON (F) mounting version Art-Net; stand-alone; DMX; sound to light via microphone; RDM Preprogrammed in: Light J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3 Projection: Beam angle: 4° Beam angle (1/10 peak): 4° Beam angle (1/10 peak): To Housing color: Black Attachment system: Mounting bracket Dimensions: Length: 44 cm Depth: 16 cm Height: 17,3 cm Weight: 6,15 kg Special product: Not designed for household room illumination	Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
LED type: 5 x 15 W high-power 4in1 QCL RGBW (homogenous color mix) 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version 1 x 5-pin XLR (F) mounting version 1 x 3-pin XLR (F) mounting version 1 x 3-pin XLR (F) mounting version 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version 1 x	Power output:	1 x PowerCON (gray), mounting version
(homogenous color mix) Flash rate: 0 - 18 Hz DMX channels: 4; 6; 8; 20; 24 DMX input: 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version Network connection: Protocol: Art-Net 3 via 2x RJ-45 etherCON (F) mounting version Control: Art-Net; stand-alone; DMX; sound to light via microphone; RDM Preprogrammed in: Light' J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3 Projection: Flicker-free Beam angle (1/2 peak): 4° Beam angle (1/2 peak): 4° Beam angle (1/10 peak): 7° Housing color: Black Attachment system: Mounting bracket Dimensions: Length: 44 cm Depth: 16 cm Height: 17,3 cm Weight: 6,15 kg Legal specifications Special product: Not designed for household room illumination	Lamp type:	LED lamp
DMX channels: 4; 6; 8; 20; 24 DMX input: 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version Network connection: Protocol: Art-Net 3 via 2x RJ-45 etherCON (F) mounting version Art-Net; stand-alone; DMX; sound to light via microphone; RDM Preprogrammed in: Light'J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3 Projection: Flicker-free Beam angle: 4° Beam angle (1/2 peak): 4° Beam angle (1/10 peak): 7° Housing color: Black Attachment system: Mounting bracket Dimensions: Length: 44 cm Depth: 16 cm Height: 17,3 cm Weight: 6,15 kg Legal specifications Special product: Not designed for household room illumination	LED type:	3 ,
DMX input: 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version 1 x 5-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version Protocol: Art-Net 3 via 2x RJ-45 etherCON (F) mounting version Art-Net; stand-alone; DMX; sound to light via microphone; RDM Preprogrammed in: Light'J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3 Projection: Flicker-free Beam angle: 4° Beam angle (1/2 peak): 4° Beam angle (1/10 peak): 7° Housing color: Black Attachment system: Mounting bracket Dimensions: Length: 44 cm Depth: 16 cm Height: 17,3 cm Weight: 6,15 kg Legal specifications Special product: Not designed for household room illumination	Flash rate:	0 - 18 Hz
1 x 5-pin XLR (M) mounting version 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version Network connection: Protocol: Art-Net 3 via 2x RJ-45 etherCON (F) mounting version Control: Art-Net; stand-alone; DMX; sound to light via microphone; RDM Preprogrammed in: Light'J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3 Projection: Flicker-free Beam angle: 4° Beam angle (1/2 peak): 4° Beam angle (1/10 peak): 7° Housing color: Black Attachment system: Mounting bracket Dimensions: Length: 44 cm Depth: 16 cm Height: 17,3 cm Weight: 6,15 kg Special product: Not designed for household room illumination	DMX channels:	4; 6; 8; 20; 24
Network connection: Protocol: Art-Net 3 via 2x RJ-45 etherCON (F) mounting version Art-Net; stand-alone; DMX; sound to light via microphone; RDM Preprogrammed in: Light'J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3 Projection: Flicker-free Beam angle: 4° Beam angle (1/2 peak): Beam angle (1/10 peak): To Housing color: Black Attachment system: Mounting bracket Dimensions: Length: 44 cm Depth: 16 cm Height: 17,3 cm Weight: 6,15 kg Not designed for household room illumination	DMX input:	
mounting version Art-Net; stand-alone; DMX; sound to light via microphone; RDM Preprogrammed in: Light'J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3 Projection: Flicker-free Beam angle: 4° Beam angle (1/2 peak): 4° Beam angle (1/10 peak): To Housing color: Black Attachment system: Mounting bracket Dimensions: Length: 44 cm Depth: 16 cm Height: 17,3 cm Weight: 6,15 kg Special product: Not designed for household room illumination	DMX output:	, ,
microphone; RDM Preprogrammed in: Light'J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3 Projection: Flicker-free Beam angle: 4° Beam angle (1/2 peak): 4° Beam angle (1/10 peak): 7° Housing color: Black Attachment system: Mounting bracket Dimensions: Length: 44 cm Depth: 16 cm Height: 17,3 cm Weight: 6,15 kg Legal specifications Special product: Not designed for household room illumination	Network connection:	. ,
SHOW 2; EASY SHOW 3 Projection: Flicker-free Beam angle: 4° Beam angle (1/2 peak): 4° Beam angle (1/10 peak): 7° Housing color: Black Attachment system: Mounting bracket Dimensions: Length: 44 cm Depth: 16 cm Height: 17,3 cm Weight: 6,15 kg Special product: Not designed for household room illumination	Control:	
Beam angle: Beam angle (1/2 peak): Beam angle (1/10 peak): Housing color: Black Attachment system: Mounting bracket Dimensions: Length: 44 cm Depth: 16 cm Height: 17,3 cm Weight: 6,15 kg Legal specifications Special product: Not designed for household room illumination	Preprogrammed in:	
Beam angle (1/2 peak): Beam angle (1/10 peak): Housing color: Attachment system: Dimensions: Length: 44 cm Depth: 16 cm Height: 17,3 cm Weight: 6,15 kg Special product: Not designed for household room illumination	Projection:	Flicker-free
Beam angle (1/10 peak): Housing color: Attachment system: Dimensions: Length: 44 cm Depth: 16 cm Height: 17,3 cm Weight: Legal specifications Special product: Not designed for household room illumination	Beam angle:	4°
Housing color: Black Attachment system: Mounting bracket Length: 44 cm Depth: 16 cm Height: 17,3 cm Weight: 6,15 kg Legal specifications Special product: Not designed for household room illumination	Beam angle (1/2 peak):	4°
Attachment system: Dimensions: Length: 44 cm Depth: 16 cm Height: 17,3 cm Weight: 6,15 kg Legal specifications Special product: Not designed for household room illumination	Beam angle (1/10 peak):	7°
Dimensions: Length: 44 cm Depth: 16 cm Height: 17,3 cm Weight: 6,15 kg Legal specifications Special product: Not designed for household room illumination	Housing color:	Black
Depth: 16 cm Height: 17,3 cm Weight: 6,15 kg Legal specifications Special product: Not designed for household room illumination	Attachment system:	Mounting bracket
Legal specifications Special product: Not designed for household room illumination	Dimensions:	Depth: 16 cm
Special product: Not designed for household room illumination	Weight:	6,15 kg
	Legal specifications	
Intended use: Show effect lighting	Special product:	Not designed for household room illumination
	Intended use:	Show effect lighting