

FUTURELIGHT POS-8 LED HCL Powerstick

LED color changing bar with 10 W RGBWA+UV LEDs (6in1)

Art. No.: 51841367

GTIN: 4026397510829



The article is no longer in our assortment.

Features:

- Equipped with 8 hexacolor LEDs in the colors red, green, blue, amber, white and UV
- Each LED can be controlled individually
- Suitable for pixel mapping applications
- Hanging as well as standing installation possible
- Functions: Static colors RGBAW+UV color mixture, color presets, preset color temperatures, automatic color change, built-in programs, dimmer, strobe effect, Master/Slave operation
- Dimmer speed (step response) adjustable
- Adjustable microphone sensitivity
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Comfortable addressing and setting via Control Board with LC display and four operating buttons
- Switch-mode power supply for operation between 100 and 240 Volts
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power up to 8 devices
- DMX control via every standard DMX controller
- 8 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Strobe effect; UV effect
- Control via stand-alone; DMX; sound to light via microphone
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
- Flicker-free
- With a beam angle of 22°

Logistic

EAN / GTIN: 4026397510829

Weight: 4,20 kg

Length: 0.58 m

Width: 0.16 m

Height: 0.22 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	85,00 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED type:	8 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
Flash rate:	0 - 30 Hz
DMX channels:	3 (HSV hue/saturation/value); 3 (HSI hue/saturation/intensity); 6; 8; 12; 48; 53
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Control:	Stand-alone; DMX; sound to light via microphone
Preprogrammed in:	Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
Projection:	Flicker-free
Beam angle:	22°
Beam angle (1/2 peak):	22°
Beam angle (1/10 peak):	33°
Housing color:	Black
Dimensions:	Length: 55,5 cm Depth: 8 cm Height: 18,3 cm
Weight:	3,70 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting