

FUTURELIGHT STB-648 LED Strobe SMD 5050

PRO LED strobe

Art. No.: 51841370

GTIN: 4026397466867









The article is no longer in our assortment.

Features:

- Equipped with 648 LEDs
- Much brighter than a 750 W Strobe
- Sound-controlled via built-in microphone
- Microphone-sensitivity adjustable via rotary-control
- Pure convection cooling via cooling ribs, no fans
- Comfortable addressing and setting via Control Board with LED display and four operating buttons with 14 segment display
- Operable in stand-alone mode or via DMX
- Brightness and flash-rate (1-30 flashes/sec) adjustable
- Feed-through output allows to power another device
- After every 8 devices the fixtures must have a renewed connection with the power mains
- DMX512 control via regular DMX-controller

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	160,00 W
Dimensions:	Width: 42 cm Depth: 22,5 cm
	Height: 16,5 cm
Weight:	4,90 kg
DMX channels:	2

Logistic

EAN / GTIN: 4026397466867 Weight: 5,40 kg Length: 0.46 m Width: 0.28 m Heigth: 0.21 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

DMX connection:	5-pin and 3-pin XLR
Flash-rate:	1-30 Hz
Sound-control:	via built-in microphone
LED number:	648
LED type:	SMD 5050
Dimensions (L x W x H):	420 x 225 x 165 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting