

## FUTURELIGHT DMB-60 LED Moving-Head

LED beam with LUMINUS CBT-90 LED and the advantages of a moving head

Art. No.: 51841801

GTIN: 4026397461794



**The article is no longer in our assortment.**

### Features:

- Extremely high light output
- Very narrow illumination angle
- Light beam can easily be centered and moved exactly
- 13, 15 or 16 DMX channels selectable
- Effect wheel with rotating 3-facet prism and 8-facet prism and frost filter
- Color wheel with 8 different dichroic color filters plus white
- Rainbow effect with adjustable speed in both directions
- Gobo wheel with 11 static gobos plus open
- With gobo shake function
- Exact positioning via 16 bit PAN/TILT movement resolution
- Dimmer
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Sound-controlled via built-in microphone
- Switch-mode power supply
- Automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with graphic LCD display and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- Power connection via Neutrik PowerCon jack and included power cable

### Logistic

EAN / GTIN: 4026397461794

Weight: 14,50 kg

Length: 0.61 m

Width: 0.43 m

Height: 0.36 m

- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- 1 powerful LED
- LUMINUS LED installed
- Control via sound to light via microphone; RDM; DMX

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	120 W
LED type:	1
LED manufacturer:	LUMINUS
Max. TILT movement:	270° positioning
Max. PAN movement:	630° positioning
DMX channels:	13
Control:	Sound to light via microphone; RDM; DMX
Beam angle (1/2 peak):	5°
Beam angle (1/10 peak):	5°
Dimensions:	Width: 34,3 cm Depth: 25 cm Height: 42,8 cm
Weight:	12,20 kg
DMX channels:	13/15/16
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	LUMINUS CBT-90
LED number:	1
Beam angle:	5°
Color-wheel:	8 dichroic filters plus open
Static gobo-wheel:	11 gobos and open
Maximum PAN-movement:	630°
Maximum TILT-movement:	270°
Dimensions (L x W x H):	343 x 250 x 428 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting