

FUTURELIGHT DMH-30 LED Moving Head

High performance LED Moving Head

Art. No.: 51841825 GTIN: 4026397420692











The article is no longer in our assortment.

Features:

- 1 extra bright 20 W LED for best luminance
- Comparable to the light output of bright 150 W discharge lamp
- Effect-wheel with 3-facet prism, 5-facet prism and 3D-prism
- Macro-function for rotating gobos/prism combinations
- Color-wheel with 7 different dichroic color filters, UV filter plus white
- Switchable color change (mode 1: only full colors, mode 2: color change at every position)
- Rainbow effect with adjustable speed in both directions
- Gobo wheel with 7 rotating gobos plus open
- All gobos can be interchanged
- Slot-in gobo-system for exchanging gobos without tools
- With gobo shake function
- Exact positioning via 16 bit PAN/TILT movement resolution
- Manual focus
- Dimmer
- Strobe effect with adjustable speed
- Random strobe effect
- RDMX (Remote DMX Addressing): DMX address setting via controller possible
- Power standby mode
- PAN angle switchable between 630° and 540°
- Switch-mode power supply
- Automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with 4-digit display and foil-keyboard for adjusting the DMX starting address, PAN/TILT Reverse, Program, Reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 56 preprogrammed scenes in Program Run for stand-alone operation
- Number of scenes in Program Run can be changed individually

Logistic

EAN / GTIN: 4026397420692

Weight: 10,90 kg Length: 0.46 m Width: 0.34 m Heigth: 0.39 m

- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- 7 built-in programs can be called up via DMX controller
- Software upload by optional FUTURELIGHT ULB-1 upload box via DMX link
- Sound-controlled via built-in microphone
- DMX control via every standard DMX controller

Technical specifications:

<u> </u>	
Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	125,00 W
Weight:	9,50 kg
DMX channels:	12
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Flash-rate:	22 Hz
LED type:	LUMINUS SST-50
LED number:	1
Beam angle:	14°
Color-wheel:	7 dichroic filters, UV-filter plus open
Rotating gobo-wheel:	7 gobos and open
Outside diameter of the gobos:	27 mm
Image diameter of the gobos:	22 mm
Length of base:	295 mm
Width of yoke:	275 mm
Height (head horizontal):	385 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting