

FUTURELIGHT DMH-80 LED Spot

PRO moving-head with 75 W LED and unique 16-facet prism

Art. No.: 51841841

GTIN: 4026397620146



List price: 1129.31 €

incl. 19% VAT.

Features:

- High PAN/TILT speed
- Optional W-DMX receiver for wireless DMX control
- Effect wheel with rotating 16-facet prism
- Exact positioning via 16 bit PAN/TILT movement resolution
- Electronic dimmer (0-100%)
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 630° and 540°
- Number of scenes can be changed individually
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Software upload by optional accessories via DMX link
- 1 powerful LED 75 W COB (chip-on-board) cold white (CW)
- Color wheel 8 dichroic filters plus open
Rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 7 gobos and open
shake effect
- Gobos changeable
- Slot-in gobo system for exchanging gobos without tools
- Can be operated in 11; 13; 17; 18 CH mode
- The device is cooled by temperature-controlled fan
- Controlling by stand-alone; DMX; RDM; Sound to light via Microphone
- Preprogrammed in Light J; LED PC-Control 512; Light Captain
- Effect: Gobo effect; Single Beam
- With a beam angle of 10 - 16°
- Multicolor LCD display for easy controlling

Logistic

EAN / GTIN: 4026397620146
Weight: 11,15 kg
Length: 0.53 m
Width: 0.38 m
Height: 0.28 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	135 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED:	1 x 75 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	Exact positioning (16 bit resolution) 270° Auto position correction (feedback)
Max. PAN movement:	Exact positioning (16 bit resolution) 540° Positioning switchable to 630° Auto position correction (feedback)
Equipment:	Gobo wheel with rotating gobos; Prism 16-fold; Focus motor-driven
Color generation:	Color wheel 8 dichroic filters plus open
Gobos:	Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 24mm Image diameter 19mm Shake effect Gobos changeable Slot-in gobo system for exchanging gobos without tools
DMX channels:	11; 13; 17; 18
DMX input:	1 x 5-pin XLR (M) mounting version
DMX output:	1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; RDM; Sound to light via Microphone; Light J; LED PC-Control 512; Light Captain
Beam angle:	10 - 16°
Beam angle (1/2 peak):	10 - 16°
Beam angle (1/10 peak):	10 - 16°
Illuminance in Lux (lx):	Narrow cold white (CW) 3m: 8334 lx, 6m: 2169 lx Wide cold white (CW) 3m: 5211 lx, 6m: 1339 lx
Housing color:	Black
Display type:	Multicolor LCD display
Dimensions:	Width: 29,9 cm Depth: 25,2 cm Height: 39,8 cm
Weight:	9,55 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination

Intended use:

Show effect lighting
