

FUTURELIGHT DMH-200 LED Moving Head

PRO beam/wash moving-head with 200 W COB LED and large zoom

Art. No.: 51841975

GTIN: 4026397604214



List price: 2438.31 €

incl. 19% VAT.

Features:

- Equipped with a powerful white 200 W COB LED
- Upgrade via optional wireless receiver module for WDMX operation (Wireless Solution - made in Sweden)
- Effect wheel with rotating 3-facet prism
- Exact positioning via 16 bit PAN/TILT movement resolution
- Motorized focus
- Autofocus
- Motorized zoom with 7.5 - 40° beam angle
- Steplessly adjustable iris
- Stepless frost-filter
- Dimmer
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Control board with graphic LCD and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power up to 8 devices
- ESDC function (Easy Service Data Check) with battery-buffered control board for operation time readouts etc. (the Li-Ion battery 3.7V, AAA, 10440 is not included)

Logistic

EAN / GTIN: 4026397604214

Weight: 24,35 kg

Length: 0.71 m

Width: 0.45 m

Height: 0.35 m

- Switch-mode power supply for operation between 100 and 240 volts
- DMX control via every standard DMX controller
- LED: 1 x COB (chip-on-board) 200 W cold white (CW)
- Color wheel 8 dichroic filters plus open
Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 7 gobos and open
- Gobo wheel with rotating gobos, 7 gobos and open
shake effect
- Gobos changeable
- Slot-in gobo system for exchanging gobos without tools
- Can be operated in 15; 17; 24; 25 CH mode
- The device is cooled by temperature-controlled fan
- Controlling by Stand-alone; DMX; RDM; W-DMX by wireless solution upgradeable; Sound to light via Microphone
- Is in EUROLITE LED PC-Control 512 software already preprogrammed
- Flicker-free projection
- Effect: Gobo effect; Single Beam

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	270 W
IP classification:	IP20
Power connection:	Mains input PowerCON (blue), mounting version Power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED:	1 x COB (chip-on-board) 200 W cold white (CW)
Max. TILT movement:	Exact positioning (16 bit resolution) 265° Auto position correction (feedback)
Max. PAN movement:	Exact positioning (16 bit resolution) 540° Positioning switchable to 630° Auto position correction (feedback)
Equipment:	Gobo wheel with rotating gobos; gobo wheel with static gobos; Prism 3-fold; Iris; Focus motor-driven; Zoom motor-driven; frost filter
Color generation:	Color wheel 8 dichroic filters plus open
Gobos:	Gobo wheel with static gobos, 7 gobos and open Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 27mm Image diameter 22mm Shake effect Gobos changeable Slot-in gobo system for exchanging gobos without tools
DMX channels:	15; 17; 24; 25
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; RDM; W-DMX by wireless solution upgradeable; Sound to light via Microphone; EUROLITE LED PC-Control 512 software

Beam angle:	7,5 - 40°
Beam angle (1/2 peak):	7,5 - 40°
Beam angle (1/10 peak):	7,5 - 40°
Housing color:	Black
Dimensions:	Width: 40,2 cm Depth: 25 cm Height: 53,4 cm
Weight:	21,55 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
intended use:	show effect lighting