

FUTURELIGHT PRO Slim PAR-12 MK2 HCL

Flat PRO LED spotlight with 12 x 10 W 6in1 LED (RGBWA+UV) without fan

Art. No.: 51842561 GTIN: 4026397590609











The article is no longer in our assortment.

Features:

- Equipped with 12 high-power LEDs in the colors red, green, blue, amber, white and UV
- Flat housing form requires minimal space when rigging
- Extremely compact housing in a beautiful design
- Second mounting bracket for safe standing installation
- Locking possibility at the brackets with large metal butterfly screws
- Functions: static colors, RGBAW+UV color mixture, automatic color changes, dimmer, strobe effect with adjustable speed, Master/Slave operation
- Addressing and setting via Control Board with four operating buttons and LED display
- Switch-mode power supply for operation between 100 and 240 volts
- P-Con terminals for power linking up to 8 units
- 12 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Strobe effect; UV effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone
- Preprogrammed in Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
- Flicker-free
- With a beam angle of 18°
- Silent operation

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord

Logistic

EAN / GTIN: 4026397590609

Weight: 5,40 kg Length: 0.26 m Width: 0.26 m Heigth: 0.31 m

Technical specifications:

| Power supply: | 100-240 V AC, 50/60 Hz |
|-------------------------|--|
| Power consumption: | 100 W |
| IP classification: | IP20 |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x P-Con (gray), mounting version |
| Lamp type: | LED lamp |
| LED type: | 12 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix) |
| DMX channels: | 6; 10 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; DMX; sound to light via microphone |
| Preprogrammed in: | Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain |
| Projection: | Flicker-free |
| Beam angle: | 18° |
| Beam angle (1/2 peak): | 18° |
| Beam angle (1/10 peak): | 32° |
| Housing color: | Black |
| Dimensions: | Width: 28 cm Depth: 12,5 cm Height: 29,5 cm |
| Weight: | 4,80 kg |
| Noise classification: | Class 0 (no noise at all) |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |
| | |