

FUTURELIGHT SVS-37.5 LED display 90x90

LED video display for outdoor use

Art. No.: 51843210

GTIN: 4026397465334



The article is no longer in our assortment.

Features:

- Modular LED video display for outdoor use, IP63
- Extra bright and colorful projection of videos, animations and graphics
- Ideal for rental companies, stage/fair construction and fixed installation
- Super-light and durable aluminum construction
- Seamless, modular display concept allows the build-up of large areas
- 37.5 mm pixel pitch
- 1024 pixels (32 x 32)
- Supports full HD 1080p
- Signal processing via onboard receiver card
- Control via optional video processor or PC software
- Ethernet-based signal distribution
- Truss support bar, signal and power cables optional

Logistic

EAN / GTIN: 4026397465334

Weight: 22,00 kg

Length: 1.01 m

Width: 0.22 m

Height: 1.02 m

Bulky product

Technical specifications:

| | |
|---------------------|-------------------------------|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 180,00 W |
| IP classification: | IP63 |
| Dimensions: | Width: 90 cm Height: 90 cm |
| Weight: | 17,05 kg |
| Resolution (W x H): | 32 x 32 pixels |

| | |
|------------------------|--|
| Pixel pitch: | 37.5 mm |
| Pixel density: | 711/m² |
| Pixel configuration: | DIP346 |
| Signal connection: | DVI/RJ45 |
| Display mode: | progressive scan |
| Brightness: | 3300 cd/m² (nits) |
| Viewing angle: | 50° horizontally |
| | 110° vertically |
| Data refresh rate: | >2400 Hz |
| Contrast level: | >8192 |
| Grey scale: | 16 bits |
| Number of displays: | max. 1280 per sending card |
| | up to 1280 x 1024 pixels |
| Protection grade: | IP63 |
| Operating temperature: | -10 to 45 °C |
| Humidity: | 10 to 95 % |
| Dimensions: | 900 x 900 mm |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |