

FUTURELIGHT SVS-25 LED display 80x80

LED video display for outdoor use

Art. No.: 51843220

GTIN: 4026397465358



The article is no longer in our assortment.

Features:

- Modular LED video display for outdoor use, IP63
- Extra bright and colorful projection of videos, animations and graphics
- Ideal for rental companies, stage/fair construction and fixed installation
- Super-light and durable aluminum construction
- Seamless, modular display concept allows the build-up of large areas
- 25 mm pixel pitch
- 1024 pixels (32 x 32)
- Supports full HD 1080p
- Signal processing via onboard receiver card
- Control via optional video processor or PC software
- Ethernet-based signal distribution
- Truss support bar, signal and power cables optional

Logistic

EAN / GTIN: 4026397465358

Weight: 22,60 kg

Length: 0.92 m

Width: 0.23 m

Height: 0.94 m

Bulky product

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	160,00 W
IP classification:	IP63
Dimensions:	Width: 80 cm Height: 80 cm
Resolution (W x H):	32 x 32 pixels
Pixel pitch:	25 mm

Pixel density:	1600/m²
Pixel configuration:	DIP546
Signal connection:	DVI/RJ45
Display mode:	progressive scan
Brightness:	5500 cd/m² (nits)
Viewing angle:	145° horizontally
	110° vertically
Data refresh rate:	>2400 Hz
Contrast level:	>8192
Grey scale:	16 bits
Protection grade:	IP63
Number of displays:	max. 1280 per sending card
	up to 1280 x 1024 pixels
Operating temperature:	-10 to 45 °C
Humidity:	10 to 95 %
Dimensions:	800 x 800 mm
Weight:	13 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting