

## FUTURELIGHT SVS-18.75 LED display 60x60

LED video display for outdoor use

Art. No.: 51843230

GTIN: 4026397465372



**The article is no longer in our assortment.**

### Features:

- Modular LED video display for outdoor use, IP63
- Extra bright and colorful projection of videos, animations and graphics
- Ideal for rental companies, stage/fair construction and fixed installation
- Super-light and durable aluminum construction
- Seamless, modular display concept allows the build-up of large areas
- 18.75 mm pixel pitch
- 1024 pixels (32 x 32)
- Supports full HD 1080p
- Signal processing via onboard receiver card
- Control via optional video processor or PC software
- Ethernet-based signal distribution
- Truss support bar, signal and power cables optional

### Logistic

EAN / GTIN: 4026397465372

Weight: 16,20 kg

Length: 0.71 m

Width: 0.21 m

Height: 0.72 m

### Technical specifications:

|                     |                               |
|---------------------|-------------------------------|
| Power supply:       | 100-240 V AC, 50/60 Hz        |
| Power consumption:  | 160,00 W                      |
| IP classification:  | IP63                          |
| Dimensions:         | Width: 60 cm<br>Height: 60 cm |
| Resolution (W x H): | 32 x 32 pixels                |
| Pixel pitch:        | 18.75 mm                      |

|                        |  |
|------------------------|--|
| Pixel density:         | 2844/m²                                      |
| Pixel configuration:   | DIP346                                       |
| Signal connection:     | DVI/RJ45                                     |
| Display mode:          | progressive scan                             |
| Brightness:            | 5000 cd/m² (nits)                            |
| Viewing angle:         | 110° horizontally                            |
|                        | 45° vertically                               |
| Data refresh rate:     | >2400 Hz                                     |
| Contrast level:        | >8192  |
| Grey scale:            | 16 bits                                      |
| Number of displays:    | max. 1280 per sending card                   |
|                        | up to 1280 x 1024 pixels                     |
| Protection grade:      | IP63   |
| Operating temperature: | -10 to 45 °C                                 |
| Humidity:              | 10 to 95 %                                   |
| Dimensions:            | 600 x 600 mm                                 |
| Weight:                | 13 kg  |
| Legal specifications   |  |
| Special product:       | Not designed for household room illumination |
| Intended use:          | Show effect lighting                         |