eurolite®

EUROLITE LED PC-Control 1024

DMX control software PC-Control with USB interface

GTIN: 4026397420036



The article is no longer in our assortment.

Description:

LED PC-Control is the ideal DMX512 software for all DJ and Architectural applications or small/medium-sized projects. It manages all LED technology-based equipment and can control any type of standard DMX appliance. The software is the most user friendly and affordable solution for DMX lighting control.

Features:

- Lighting control software for LJs, VJs, and lighting professionals
- Incl. USB interface for 1 DMX universe (PC 512) or 2 DMX universes (PC 1024)
- Supports Windows 7, Mac OS X, Linux and Android
- Graphic and user-friendly live board for touchscreens and smartphones
- Free SmartBoard DMX App available at the App store for Android and IOS
- Remotely trigger scenes and programs via WIFI with your smartphone or instantly change RGB colors of your LED lights and much more
- Automatic program generator with X-Pan, Y-Tilt and RGB effects
- Graphic patch editor for DMX fixture addressing
- Quick fixture profile editor with 3000 files (libraries) included
- Advanced Matrix editor to allow all LED configurations
- Multiple menu languages (e.g. French, English, German)
- Full RGB (W/A) color and dimmer management and rendering
- Graphic 2D edition of fixtures
- Up to 5120 channels with several plugged interfaces
- Colors, dimmer, speed, black out and pause can be managed in live mode
- Fade-in time between programs and scenes
- Multiple program triggers



EAN / GTIN: 4026397420036 Weight: 0,32 kg Length: 0.20 m Width: 0.14 m Heigth: 0.06 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- DMX output speed signal can be configured for perfect DMX line stability and full compatibility with any electronic fixtures (Mab, Break, Delay, frequency 1 to 45 Hz)
- Strong aluminum housing suitable for wall mounting
- Minimum configuration required:
- Operating system: Mac Os X, Windows 32 or 64 bit (2000, XP, Vista, 7)
- CPU: 1 GHz, RAM memory: 512 Mb, hard disk space: 150 MB
- Can transmit up to 1024 DMX channels
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

DMX channels:	Output 1024
USB port:	USB 2.0, type B
Weight:	0,23 kg